SURVEY &	
GENONU MEDIATION	1
<u> </u>	

NOV 07 1994

COMMISSION

Chippewa County Remonumentation Corner

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74. Mich. P.A. 1970

For corners in	Filing Requir	ement of Act 74, Mich. P.A	. 1970
Chippewa	1	· ·	
(County)	Located In:	Corner Code ##	
			\$ 7.00 LAND CORNER
Public Land Survey	T 45N R 2W	<u>1-11</u>	\$ 2.00 MSSR
	T R		18 OCT 94 1:07 P.M. RECEIPT# 700
	T R		RECEIVED FOR RECORD
	T R		SHIPPEWA COUNTY - STATE OF MICHIGAN
2. Property Controlling S	T R,		SHARON H. KENNEDY, REGISTER OF DEEDS
in Section S	<u> </u>		
Miscellaneous S	<u> </u>		Register of Deeds Stamp & File Number
Property in Sec. S	Т R		
4. Lot No, Recorde			A B C D E F G H I J K L
5. Private Claims			2 6 5 4 3 3
			3 3 3 2 1
			4 7 8 9 10 11
ı, William L. Karr , in a fi	iold support on May 1"	1. 40.93	
do hereby certify that under requiremen			ed 5
in lines 1 and 2 above were in conform	mance with regulations an	id rules therefore as required in t	he ° 18 17 16 15 14 13
current manual of survey instructions of	of the United States Depar	tment of the Interior, Bureau of La	nd 7
Management or by a decree of a Court of above were in conformance with the rule			
Court of Law; established, re-establ			
expressed below:		, , , , , , , , , , , , , , , , , , , ,	10 30 29 28 27 26 25
NOTE: Not more than 4 corners,	all in the same town ar	nd range, may be recorded	11
on this certificate.		• • • • • • • • • • • • • • • • • • • •	12 31 32 33 34 35 36
			13
 A. Description of original monume 	•	The state of the s	•
(I-11) Corner Common	to Sections 26, 3	35, 34 & 27 (T45N-R2V	<u>v</u>)
			iron pin. Recorded in
Liber 2, Page 23	8 of the Chippewa	a County Corner Record	ds.
1984 William L. Karr,	L.S. 27450, four	nd a railroad spike th	hat matched a cut off
power pole as ca	Tred tot in Whor.	notes. Replaced with	h a ½" iron and cap #27450
			ewa County Corner Records.
Twin 6" Spru		88.45′	
6" Jack Pine 8" Jack Pine	S26°W	9/•80	
8" Jack Pine Power Pole (E14) N52°W	85.13′ 49.91′	
B. Description of corner evidence	found and/or method a		lishing corner:
(I-11) This corner		erpetuated as part	_
Remonumentation Progra		arpoonded as pare	or the dilppewa county
Temorian Strategical Trogra			
Found ½" iron with	L.S. cap #2745	0 and three record	witness objects. Accepted
corner position as fou			
-		3	MINIMINIAN CONTRACTOR OF THE PROPERTY OF THE P
			WHILE BENY COLUMN
			10000 COOP 1000 1000 1000 1000 1000 1000 1000 1
			10/1/44 /Ear =
	•		
	•		ting the position of the corner:
C. Description of monument for co	orner and accessories e	established to perpetuate loca	ting the position of the corner
			the intersection of old road
beds.	*		
			Messes
Witnesses: 6" Jack Pin		97.80' (existing P	K)
8" Jack Pin	1	85.13' (existing P	
Power Pole	,	49.91' (existing P	K) J
. 9" Tamarack	N48°E	32.33′	* LAND *
			SURVEYOR *
			No.
			27450
1	1		ERECOUR
1 -00.	\square \cup		LAND
Signed by Wine	The Kam	Date	11194
	. ! <i>1</i>		1708-00

Surveyor's Michigan License No. 27450

NOTE: Bearings are compass bearings corrected for declination.

Distances are to a nail in side of witness objects unless noted.

1700 00

REVISED MAN 28, 1971

REVISED JAN., 1983