

## CHIPPEWA COUNTY REMONUMENTATION CORNER

RECEIVED FOR RECORD  
CHIPPEWA COUNTY  
STATE OF MICHIGANLAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

93 DEC -3 PM 3: 58

For corners in  
Chippewa

(County)

Located In:

Corner Code ##

1. Public Land Survey

T 47N R 1W

D-7/E-7 #2

T R

T R

T R

S T R

2. Property Controlling  
in Section

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Keith R. Waters

September 9, 1993

I, Keith R. Waters, in a field survey on September 9, 1993, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

D-7/E-7 Witness Corner to Meander Corner Sections 17 &amp; 20, T47N, R1W.

Original meander corner was a 10" tamarack 33.71 chains (2224.86') west of Section corner common to Sections 16, 17, 20, & 21.

Subsequent County Surveyor notes show corner 2112' west of Section corner common to Sections 16, 17, 20, & 21.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

D-7/E-7 (T47N, R1W)

This corner is being re-established as part of the Chippewa County Remonumentation Program.

Found no evidence of corner or its accessories. Re-established corner 2060 feet west of Section corner common to Sections 16, 17, 20, & 21, T47N, R1W, approximately 25 feet from shore of Saint Marys River. North-south position was determined using record angle (88°05') from east line of Section 17, as shown in old Chippewa County Surveyor notes. Bearing of line between Sections 17 & 20 is within approximately 12 minutes of extension of line between Sections 16 & 21.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-7/E-7 (T47N, R1W)

Corner is a 3/4" x 24" rebar with 3/4" aluminum Chippewa County Remonumentation cap approximately 25 feet from the shore of the Saint Marys River. Witnesses:

3" Black Ash, N44°W 19.22'  
9" White Birch, N04°E 55.94'  
12" Cedar, N06°E 59.57'  
5' Black Ash, S78°E 48.14'

Note: Distances are to a nail and tag in the side of the witness object. Bearings are compass bearings corrected for declination. Trees are blazed and painted. Distances measured with EDM.

Signed by Keith R. WatersDate 11-30-93Surveyor's Michigan License No. 33142