

FEB 2 3 2001

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Corner Code #

Chippewa County Remonumentation Corner \$7.00 LAND CORNER

SECTION For corners in

Chippewa County Located in: 1. Public Land Survey **T47N R2E** R т Т R Ŧ R 2. Property Controlling S Т R in Section S Т R Miscellaneous

\$2.00 MSSR 9 FEB 2001 10:27:35 AM Receipt #1201 RECEIVED FOR RECORD

CHIPPEWA COUNTY - STATE OF MICHIGAN SHARON H. KENNEDY, REGISTER OF DEEDS

BOOK 11 PAGE 216

Register of Deeds Stamp & File Number



, Recorded Plat

S

5. Private Claims


Property in Sec.

I, Larry R. Rogers, P.S., in a field survey on December 8, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

T

R

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.



A. Description of original monument and accessories and/or subsequent restoration: (B-5) 1/4 Corner common to Sections 7 and 8, Township 47 North, Range 2 East. John Muliett placed original 1/4 Section post in 1845 and established the following witnesses: 8" Sugar N62W 21 lks and 12" Sugar S58E 30 lks.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: (B-5) 1/4 Corner common to Sections 7 and 8, Township 47 North, Range 2 East. This corner is being perpetuated as part of the Chippewa County Remonumentation Program

Found no evidence of original corner or any subsequent restoration. Used single proportionate measurement to reestablish corner position. Distances to Southeast and Southwest corner of Section measure 2612.87 feet (GLO = 2640 feet)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: (B-5) 1/4 Corner common to Sections 7 and 8, Township 47 North, Range 2 East. Corner is a 3/4" iron with stamped aluminum Chippewa County Remonumentation cap.

Witnesses:

8" Yellow Birch N40°W 27.90 feet 7" Maple N65°E 8.60 feet 29,22 feet 18" Maple S64°E 5" Maple S80°W 36.24 feet

All trees are blazed and painted.

OF MICHIGAN ARRY R. ROGERS and Surveyor NO. 29251 LAND

Bearings are magnetic compass bearings. All distances are to a nail and tag in the side of the witness object unless otherwise noted.

Signed by

Larry R. Rogers, P.S.

Surveyor's Michigan License No. 29251

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
PAGE TIENSED JAN. 1983

Date