FEB 2 3 2001

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Chippewa County Remonumentation Corner

For corners INTON

5. Private Claims

Chippewa County	Located	in:		Corner Code #
Public Land Surv	<i>r</i> ey	T47N T T T	R2E R R R	C-6
Property Controll in Section Missellensein	s	T T	R R	ATE OF MICHIGA
Miscellaneous Property in Sec.	· S S	Ţ	R R	LARRY R. ROGERS Land Surveyor
4. Lot No.	, Recorded Plat		# 1	NO.

MICHIGAN ARRY R. ROGERS nd Surveyor NO. 29251 LAND

I, Larry R. Rogers, P.S., in a field survey on December 01, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

\$7.00 LAND CORNER


\$2.00 MSSR

9 FEB 2001 10:30:00 AM Receipt #1201 RECEIVED FOR RECORD CHIPPEWA COUNTY - STATE OF MICHIGAN

SHARON H. KENNEDY, REGISTER OF DEEDS

PAGE 222 BOOK 11

Register of Deeds Stamp & File Number



A. Description of original monument and accessories and/or subsequent restoration:

(C-6) 1/4 Corner common to Section 17 and 18, Township 47 North, Range 2 East.

The original corner was placed in 1845 by John Mullett. In 1988, W.L. Karr, P.S. 27450 re-established corner at Page midway and on line between the Northwest and Southwest corner of Section 17 and filed a LCRC in Liberal at Page May 2015 Corner Records. The original corner was placed in 1845 by John Mullett, In 1988, W.L. Karr, P.S. 27450 re-established corner position

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner; (C-6) 1/4 Corner common to Section 17 and 18, Township 47 North, Range 2 East. This corner is being perpetuated as part of the Chippewa County Remonumentation Program.

Found 1/2" iron pin set by Karr and three witnesses from 1988. Accepted corner position as found and established one new witness.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: (C-6) 1/4 Corner common to Section 17 and 18, Township 47 North, Range 2 East

Corner is a 1/2" iron pin 3" below grade and 2 feet West of the centerline of Brasser Road (gravel).

Witnesses:

7" Sugar Maple N47°W 60.39 feet (Existing) 6" Sugar Maple S76°E 29.54 feet (Existing) 12" Sugar Maple S70°W (Existing) 65.07 feet West stem of Twin 8" Maple N49°F 60.92 feet

Bearings are magnetic compass bearings. All distances are to a nail and tag in the side of the witness object unless otherwise noted.

Signed by Larry R. Rogers, P.S.

Surveyor's Michigan License No. 29251

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971

RUIGK 11 PAGE 22 REVISED JAN. 1983

RUIGK 11 PAGE 22 REVISED JAN. 1983