

FEB 23 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
Chippewa County Remonumentation Corner

For corners in

Chippewa County

Located in:

Corner Code #

1. Public Land Survey

T47N R2E E-6

2. Property Controlling
in Section

S

T

R

3. Miscellaneous
Property in Sec.

S


T

R

4. Lot No.

Recorded Plat

5. Private Claims



I, Larry R. Rogers, P.S., in a field survey on December 01, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(E-6) 1/4 Corner common to Sections 16 and 17, Township 47 North, Range 2 East.

The original corner post was placed in 1845 by John Mullett. 1908 County Surveyor notes show the 1/4 corner 2605 feet from both the Northwest and Southwest corners of Section 16. In 1992, Larry R. Rogers, P.S. 29251 re-established the 1/4 corner midway between the Northwest and Southwest corners of Section 16 and on the centerline of Townhall Road. A new LCRC was filed in Liber 9 at Page 126 of Chippewa County Corner Records.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(E-6) 1/4 Corner common to Sections 16 and 17, Township 47 North, Range 2 East.

This corner is being perpetuated as part of the Chippewa County Remonumentation Program.

Recovered Rogers' 1/2" capped iron pin 6" below grade and in the centerline of North - South Townhall Road (gravel) and found two previous witnesses intact. Accepted corner position as found and established two new witnesses. Distances to Section corner to North and South measure 2606.5 feet (C.S. = 2605 feet).

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(E-6) 1/4 Corner common to Sections 16 and 17, Township 47 North, Range 2 East.

Corner is a 1/2" x 24" iron pin with P.S. cap #29251 6" below grade and in the centerline of Township Road. Corner falls 5 feet South of a row of small spruce trees to the West.

Witnesses:

Utility Pole (SU1/27/57)	S14°W	215.08 feet	(Existing)
Utility Pole	N01°W	176.99 feet	(Existing)
4" Maple in clump	N28°E	63.40 feet	(New)
4" Spruce	S05°E	141.48 feet	(New)

Bearings are magnetic compass bearings. All distances are to a nail and tag in the side of the witness object unless otherwise noted.

Signed by

[Signature]
Larry R. Rogers, P.S.

Surveyor's Michigan License No. 29251

Date

29 DEC 2000

\$7.00 LAND CORNER

\$2.00 MSSR

9 FEB 2001 10:33:40 AM Receipt #1201

RECEIVED FOR RECORD

CHIPPewa COUNTY - STATE OF MICHIGAN

SHARON H. KENNEDY, REGISTER OF DEEDS

BOOK 11 PAGE 234

Register of Deeds Stamp & File Number

