SURVEY & REMONUMENTATION

FEB 2 3 2001

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

SECTION

Chippewa County Remonumentation Corner

\$7.00 LAND CORNER

For	corners	in

Chippewa County

1. Public Land Survey

2. Property Controlling

Property in Sec.

in Section

3. Miscellaneous

Located in:	Corner Code#
T47N R2E	G-7

Т

T

Т

Т

S

S

S

s

R

R

R

R

\$2.00 NSSR 9 FEB 2001 10:49:32 AH Receipt #1201 RECEIVED FOR RECORD CHIPPENA COUNTY - STATE OF MICHIGAN SHARON H. KENNEDY, REGISTER OF DEEDS

еллк 11

PAGE 245

Register of Deeds Stamp & File Number

, Recorded Plat 5. Private Claims

I, William L. Karr, P.S., in a field survey on December 6, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration: (G-7) Section Corner Common to Sections 16, 15, 22 and 21, Township 47 North, Range 2 East.

1845 J. Mullett, D.S. set post.

Fir 6 N12E 19 Cedar 8 S71W 19

1915 and 1917

OVUME F.H. Brown, County Surveyor notes corner as an original. Numerous surveys in Sections 24, 16 and 15 by Brown at different dates all note a deflection angle at the North 1/4 corner of 2°54' South of a line extended from the Northwest Section corner through the North 1/4 corner . A distance of 2703.00 feet between the North 1/4 corner and the Northeast corner of Section 21 is also noted.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: (G-7) Section Corner Common to Sections 16, 15, 22 and 21. Township 47 North, Range 2 East. This corner is being re-established as part of the Chippewa County Remonumentation Program.

Found no evidence of the original corner or subsequent restoration. Reset the corner at the record deflection angle (2°54' South) and record distance (2703.00 feet) from 1/4 corner 16/21. Distance North to 1/4 corner 16/15 is 2637.46 feet

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: (G-7) Section Corner Common to Sections 16, 15, 22 and 21, Township 47 North, Range 2 East.

Set a 3/4" x 48" iron with stamped aluminum Chippewa County Remonumentation Corner Cap and falls on brush line to the North and East.

Witnesses:

W. Birch 14"	N17°E	45.00 feet
Y. Birch 5"	S77°E	31.06 feet
Mapie 8"	S13°W	13.91 feet
W. Birch 16"	N70°W	39.61 feet
Squared nost	North	1.00 foot

Bearings are magnetic compass bearings. All distances are to a nail and tag in the side of the witness object unless otherwise noted.

Signed by William L. Karc, P.S. Surveyor's Michigan License No. 27450

KARR IAND JRVEYOL