

Surveyor
REMONUMENTATION

NOV 18 1997

COMM

CLARE COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

RECEIVED

#230-97
97 NOV -4 PM 3:15

REGISTER OF DEEDS
CLARE COUNTY
CAROL A. McAULAY

For corners in

CLARE

(County)

Located in:

Corner Code #

1. Public Land Survey

T18N R 6W

A-7

T R

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, MARK R. ROBISON, in a field survey on July 1, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- 1837 Hodgson
- Set Post Cor. Sec.'s 13 & 24
- Wit-Beech 8" S22W 42
- Beech 7" N67W 21
- 12-35 Johnson CSR 2-86 & 2-87
- Stake, Broken Tile, dishes, iron, & c.
- Wit-Pine 36" S30E 81
- Fence Post 8" N48E 61

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 3/4" x 24" C.I. in broken clay tile.

See dossier for detailed report.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" x 36" rerod with Clare County Remonumentation Cap marked P.S.#27458 in clay tile. Accepted as best available evidence of the perpetuation of the County Surveyor Corner.

Witnesses:

- N74E 61.38', N&T, 7" Balsam
- N54E 48.46', N&T, 12" R. Pine
- East 39.34', N&T, 12" R. Pine
- S48E 44.50', N&T, 12" R. Pine

Signed by

Mark R. Robison

Surveyor's Michigan License No. 27458

Date 10-31-97

APPROVED LAND CORNER
P.A. 345 of 1930
Clare County

Chairman *Paul S. Leph*

Date 9-16-97

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

