

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Crawford

(County)

Located In

Corner Code #

1. Public Land Survey

T 26N R 2W L-4

2. Property Controlling
in Section

S 12 T 26N R 2W 6

3. Miscellaneous
Property in Section

S T R

S T R

4. Lot No:

Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on October 10, 2005 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

L-4 This corner position was not established during the original government survey.

6- This corner position was not established during the original government survey.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

L-4 Established the center of section 12 at the intersection of the North-South and East-West quarter lines.

6- Established the Southwest corner of the Northeast quarter of the Northeast quarter of section 12 as per B.L.M. instruction for the subdivision of a section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-4 Set 1" X 48" pipe with P.S. Cap #33981

Wit: 8" Tamarack N48°E 45.59'
12" R. Pine S78°W 12.45'
4" W. Pine S62°E 36.22'
½" Iron Rod N68°E 11.25'
½" Iron Rod S24°E 19.20'
4" Tamarack N33°W 29.94'
Blue Carsonite Post North 1'±

6- Set 5/8" X 32" iron rod with P.S. cap #33981

Wit: 8" Maple N84°W 38.00'
7" Spruce S09°W 31.85'
8" W. Pine N37°E 43.21'
½" iron N53°E 4.95'
P. Pole S64°W 22.85'
Blue Carsonite Post North 1'±

Signed by:

Carl T. Kiiskila

Date:

11/29/05

Surveyor's Michigan License No.:

33981

