

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

or corners in

Crawford
(County)

Located In:

Corner Code //

Public Land Survey

T 27N R 1W

H-11

T R

T R

T R

Property Controlling
in Section

S T R

Miscellaneous

S T R

Property in Sec.

S T R

Lot No. Recorded Plat

Private Claims

STATE OF MICHIGAN
COUNTY OF CRAWFORDFILED FOR RECORDING
12th DAY OF June 15 1990
9:30 am, in LIBER 2
PAGE 355Notarized & Witnessed
by

Register of Deeds Stamp & File Number

Norman C. Caldwell field survey on March 19 90
I hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

OTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Description of original monument and accessories and/or subsequent restoration:

(H-11) Post set by Pettibone, July 23, 1852.
Spruce Pine 13" S03°E 1.07 (70.62')
Y. Pine 30" S48°W 2.08 (137.28')

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(H-11) LaGuire, Sep. 17, 1934, placed pipe & conc. block from both orig. BTs.
Parker, LS 16939, fnd. 1/2" pipe Oct, 9, 1974.
N10°E 13.9' 6" J. Pine
N80°E 15.0' 6" J. Pine
S45°W 12.7' 10" J. Pine
rec. in L 2, pg 107

Description of monument for corner and accessories established to perpetuate locating the position of the

(H-11) 1/4 cor 27&34, T27N-R1W

Fnd. 1 1/2" pipe from rec. L 2, pg 107 by Parker. Cut his BTs to clear for G.P.S. antenna. And is accepted as a careful & faithful perpetuation of the position of the orig. corner.
North 1' Carsonite Witness Post N60°E 29.0' 2" well pipe (M.W. #3)
S48°W 138.0' 1/2" bar w/12018 cap in S85°E 47.0' 6" J. Pine
top of 24" Y. Pine stump
(orig. BT)
N30°E 39.6' 6" J. Pine

Signed by

Date

April 26, 1990

Surveyor's Michigan License No.

12018

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

