

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF --:	LOCATED IN --:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 28 N. R. 2 W.	E-12; I-11; I-13
2. PROPERTY CONTROLLING IN SECTION	T. N. S. R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S. R. E. W.	
4. LOT NO.	RECORDED PLAT	
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on June 19, 1979, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on , 19 , found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- E-12 Set corner by proportionate measurement between section corner; taking into account the deflection at $\frac{1}{4}$ corner per the U.S. record. Unable to identify a previous corner.
- I-11 Found corner as previously established by unknown but used in surveys in adjoining sections. Falls at road intersection.
- I-13 Found $1\frac{1}{2}$ " pipe in center of N-S road, as established in 1935 survey by Marcus Schaaf.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-12	I-11	I-13
Set DNR Mon. & Cedar Post	Left $1\frac{1}{4}$ " pinched pipe in place	Set DNR Monument
4" J. Pine N73°E 17.42	10" Poplar N74°E 25.8	9" J. Pine S12°E 187.75
6" J. Pine S11°E 29.60	10" Poplar N41°W 29.0	10" Oak S80°W 93.7
		Cedar Post West 20.0

SIGNED BY

Kenneth J. Ostling

DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES.

SIGNED BY

CHIEF OF SURVEY PARTY

DATE

APPROVED AND SIGNED BY

MICHIGAN REGISTERED LAND SURVEYOR

DATE

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO.

CRAWFORD COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET