

MAR 29 2000

SECTION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

CRAWFORD

(County)

Located In:

Corner Code ~~##~~

STATE OF MICHIGAN  
CRAWFORD COUNTY  
RECORDED

13 DEC 99 9:48 A.M.

SANDRA MOORE  
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

1. Public Land Survey T 28N R 3W K - 11  
T R  
T R  
T R  
2. Property Controlling S T R  
in Section S T R  
3. Miscellaneous S T R  
Property in Sec. S T R

4. Lot No. , Recorded Plat  
5. Private Claims

LIBER 4 PAGE 32

Marvin E. Myers, in a field survey on April 9, 1999, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

James H. Mullet, D.S. Norman F. Parker R.L.S.#16939 C.F. Roser, Survey Chief  
G.L.O. 1839 Unrecorded survey of Section 28 Michigan State Highway Department  
Mon. - Post Mon: 1/2" bar & post Mon: Found 1/2" iron bar below ground surface  
Wit: none provided Wit: 37" twin White Pine N33°E 64.1' Wit: 37" twin White Pine N33°E 64.1'  
8" Spruce S15°W 35.5' 8" Spruce S15°W 35.5'  
9" Birch S60°W 27.2' 9" Birch S60°W 27.2'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2" bar of record 0.3' below surface ±70' SE of Curve in County road in line with Centerlines North and West. Found 37" Twin White Pine N33°W 64.1', Found 8" Spruce S15°W 35.5'. Accepted 1/2" bar as the best available evidence of the position of the original corner. Replaced 1/2" bar with Standard Crawford County Monument.

CRAWFORD COUNTY  
PEER GROUP APPROVAL

DATE Sept 10, 1999

Marvin E. Myers  
Marvin E. Myers, P.S.  
County Surveyor

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Mon: Standard Crawford County Corner.  
Wit: Found spike in a blazed 14" Ash N80°E 20.60'  
Found spike in a blazed 8" Ash S02°E 22.32'  
Set spike in 3" Balsam N43°W 6.79'  
Set spike in 4" Balsam S67°E 25.27'  
Set Carsonite Post South 2"±



Signed by Marvin E. Myers

Date NOV 29, 1999

Surveyor's Michigan License No. 31600