

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. 28 N. R. 4 W.		E-13; G-12
2. PROPERTY CONTROLLING IN SECTION 33, T. 28 N. R. 4 W.		2; 15
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____ S., R. _____ E. W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on July 11, 1973, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 19, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- E-13 Found Houghton tile at corner.
- G-12 Found concrete tile monument as established in early county survey.
- 2 Set by standard survey procedure for subdivision of sections.
- 15 Set by standard survey procedure for subdivision of sections.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-13	G-12	2
Left conc. filled tile in place	5/8" Rod in conc. filled tile	2 1/2' of 1" pipe
7" R. Oak N85E 9.0'	6" Maple S77E 7.0'	4" R. Oak N08W 23.0'
6" R. Oak N33W 8.6'	7" Maple S40W 14.2'	6" S. Maple N71W 25.1'
32" W.P. Stp. N49W 35.3'		
15" W.P. Stp. S38W 8.9'	15	
	Set 2 1/2' of 1" pipe	
	6" W. Oak S70W 53.3'	
	30" W.P. Stp. N30W 16.9'	


SIGNED BY Kenneth J. Ostling DATE 3-15-74

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR



SURVEYOR'S MICHIGAN REGISTRATION NO. _____