

REMONUMENTATION
APR 06 1995
COMMISSION

2 - 310

CHARLEVOIX COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
ALSO ACT 345, PA 1990

STATE OF MICHIGAN
COUNTY OF CHARLEVOIX
RECEIVED FOR RECORD

1994 DEC 22 PM 1:52

Charlene M. Boskin
REGISTER OF DEEDS

For corners in CHARLEVOIX (County)
Located In: _____ Corner Code # _____

1. Public Land Survey	T	32N	R	4W	A-2
	T		R		
	T		R		
	T		R		
2. Property Controlling in Section	S		T		R
	S		T		R
3. Miscellaneous Property in Sec.	S		T		R
	S		T		R

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Wayne E. Boss, in a field survey on September 27, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Set qr. Section post	Fd. qr. Section post	Set 1/2" road & cap
1. Sugar 18" N12°W 18	Re-wit.	Witnesses:
2. Hemlock 30" S31°E 33	1. Sugar 18" N12°W 18	6" Maple N40°W 5.65'
John Mullett May 1840	2. Hemlock 30" S31°E 33	6" Maple N35°E 16.60'
	E.A. Robinson 1902	7" Ash S30°W 24.50'
		7" Maple S30°E 19.30'
		John E. Ferguson 1988

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found no evidence of G.L.O. witnesses or subsequent restoration. G.L.O. to A-1, 2640 meas. 2640.05'. G.L.O. to A-3, 2640 meas. 2641.03'.

Found 1/2" rod and cap set midway between section corners on east section line and witnesses, as recorded in corner recital in L 2, Page 236.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-2 Charlevoix County Mon. set replacing 1/2" rod & cap.
1. Spk. in Face 6" Maple N40°W 5.65'
2. Spk. in Face 6" Maple N35°E 16.60'
3. Spk. in Face 7" Basswood S30°W 24.50'
4. Spk. in Face 7" Maple S30°E 19.32'
And is accepted as a careful and faithful reestablishment of the position of the original corner

Charlevoix Co. Surveyor
APPROVED
Signature Wayne E. Boss
Date: Dec 14 1994
Public Act 345 of 1990

Signed by Wayne E. Boss Date December 14, 1994
Surveyor's Michigan License No. 20703

