

SURVEY & REMONUMENTATION

OCT 18 1996

COMMISSION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN
COUNTY OF CHARLEVOIX
RECEIVED FOR RECORD

96 OCT 14 AM 10:25

Charles M. Parker
REGISTER OF DEEDS

For corners in

Charlevoix & Antrim Located In: Corner Code #
(County)

- | | | |
|------------------------------------|-----------|-------------|
| 1. Public Land Survey | T 32NR 4W | <u>G-13</u> |
| | T 31NR 4W | <u>G-1</u> |
| | T R | |
| | T R | |
| 2. Property Controlling in Section | S T R | |
| | S T R | |
| 3. Miscellaneous Property in Sec. | S T R | |
| | S T R | |

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, James E. Evans, in a field survey on Nov. 8, 19 95 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

- A. Description of original monument and accessories and/or subsequent restoration:
G-13 CORNER COMMON TO SEC 33 & 34 T32N-R4W and SEC 3 & 4 T31N-R4W

GLO: 20" Beech for corner
1840 by John Mullett

Unknown date
E. A Robinson
Found Beech corner

LCRC 5-5-77
by Gerald R. McKelvey
Set 5/8" X 30" iron rod
tag 12" Maple S70°E 5.84'
tag 4" Maple clmp N52°W 12.71'
tag 4" Maple clmp S50°W 23.57'

April 1981 Norman F. Parker PS
#16939 set 1/2" bar from
Robinson notes
Blazed 6" Maple N37°E 54.40'
10" Maple S75°E 17.80'
8" Maple N45°W 30.60'

±1906 E. K. Robinson
Book 6 Pg. 18
Found 20" Beech corner
12" Beech S32 1/2°W
45.56 lks (30.03')

26" Hemlock S20°W
86 lks (56.76')

- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 5/8" x 30" Iron

Replaced with Charlevoix County cast iron monument

GLO to F-13 = 2640'
Robinson = 2626.45'
Meas = 2627.71'

GLO to H-13 = 2640'
Robinson = 2646.45'
Meas = 2626.55'

Charlevoix Co. Surveyor
APPROVED
Signature May C. Feindt
Date: 10-10-96

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set Charlevoix County monument at Robinson/McKelvey position

11" Maple N35°W 31.16' nail & cap #16034
10-14" Tw. Maple S05°W 19.54' nail & cap #16034
8" Maple Clmp N88°E 5.08' nail & cap #16034
6" Maple S32°W 14.43' nail & cap #16034
10" Maple S90°W 26.21' nail & cap #16034

And is accepted as a careful and faithful reestablishment of the position of the original corner.

Signed by James E. Evans
Surveyor's Michigan License No. 22431

Date 10-10-96

