

FEB 22 2001

STATE OF MICHIGAN
COUNTY OF CHARLEVOIX
REGISTERED DEEDS

SECTION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

96 DEC 11 PM 3:07

Charles M. Chamberlain
REGISTER OF DEEDS

For corners in
Charlevoix

(County)

Located In:

Corner Code #

1. Public Land Survey

T 32N R 7W
T 33N R 7W

I-1

I-13

2. Property Controlling
in Section

S T R
S T R

3. Miscellaneous
Property in Sec.

S T R
S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	16	17	18	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

Wayne E. Boss, in a field survey on NOVEMBER 8, 1996, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

I-1 GLO JUNE 1839

JOHN HODGSON

SET POST COR. SEC. 34 & 35

T33N-R7W COMMON TO SEC.

2 & 3 T32N-R7W.

1. SUGAR 10 N6W 16

2. BEECH 12 N36E 18

1" PIPE SET BY UNKNOWN

NO TIE TO GLO

BOLT SET INSIDE PIPE BY UNKNOWN

SPIKE SET OVER BOLT BY UNKNOWN

COR. USED BY S. CHAMBERLAIN
TO COMPUTE LOCATION FOR
CORNER J-1

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I-1 1 FT. SPIKE FD. OVER 1/2" X 18" BOLT FD. IN A 1" PIPE. NO WIT. FD. DIST TO TOP OF BANK OF LAKE CHARLEVOIX TO THE WEST FITS GLO DIST TO PROBABLE E-W LOCATION OF MEANDER CORNER. GLO DIST TO M.C. IS 1617'.

Charlevoix Co. Surveyor

APPROVED

Signature *Mary C. Bennett*

Date: *Nov 13, 1996*

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-1 & I-13 I-1 T32N-R7W CORNER COMMON TO I-13 T33N-R7W

CHARLEVOIX CO. MON. SET IN MON. BOX ALSO SET.

3. CTR. TELE. RISER S75E 48.40'

4. SPK. & TAG SET IN NORTH GATE POST N75W 55.57'

5. SPK. & TAG SET IN 10" PINE S75W 53.08'

6. SPK. & TAG SET IN 8" ASH S20W 84.82'

AND IS ACCEPTED AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER.



Signed by

Date

Surveyor's Michigan License No.

20703

LIBER

003

PAGE

81

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971

REVISED MAY 14, 1975

REVISED JAN., 1983

This should have been entered in the 1000 series