

FEB 22 2001

STATE OF MICHIGAN
COUNTY OF CHARLEVOIX
RECEIVED FOR RECORD

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

00 DEC 21 AM 9:02

For corners in

Charlevoix

(County)

Located in:

Corner Code #

1. Public Land Survey

T 33N R 8W

E-4

2. Property Controlling
in Section

S

T

R

3. Miscellaneous

S

T

R

Property in Sec.

S

T

R

4. Lot No. , Recorded Plat

5. Private Claims

I, Wayne E. Boss, in a field survey on November, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

E-4 October 22, 1841 Charles W. Cathcart, D.S.
Found Lynn 10" in position of 1/4 post

Sometime after 1994 John E. Ferguson, P.S.
Found ranger iron and witnessed with nails as follows
1) 20" W Ash S65°E 48.45'
2) 16" W. Ash East 39.45'
3) 24" W. Ash South 27.0'
4) 10" Poplar N85° W 14.72

June 14, 1994 Arthur Ranger, P.S.
Placed 1/2" intersection at 4 way fence intersection
no witnesses noted

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
E-4 November 7, 2000

Found 1/2" iron and cap at fence and way fence intersection
found witnesses

1) 20" W Ash S65° E 48.45' found nail
2) 16" W. Ash East 39.45' found nail
3) 24" W. Ash South 22.0" found nail
4) 10" Poplar N 85° W 14.72 found nail

E-5 to E-4 GLO 40 chains (2640') measures 2643.61'
E-4 to E-3 GLO 40 chains (2640') measures 2653.43'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
E-4 Placed Charlevoix County steel marker

1) 20" W Ash S65° E 48.45' found nail
2) 16" W. Ash East 39.45' found nail
3) 24" W. Ash South 22.0" found nail
4) 10" Poplar N 85° W 14.72 found nail

And is accepted as a careful and faithful reestablishment of the position of the original corner.

Signed by

Date

Surveyor's Michigan License No.

Charlevoix Co. Surveyor
APPROVED

Signature Mary C. Feendt
Date 12-7-00

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												