99 DEC 17 AM 9: 43

LAND CORNER RECORDATION CERTIFICATE Clare 13. Proto Filing Requirement of Act 74, Mich. P.A. 1970 For corners in REGISTER OF DEEDS **CHARLEVOIX** Located in: Corner Code # (County) - 1 mm = 1 g g \ . . . 1. Public Land Survey T_39N_R_10W I-11 R FES CEZIMI 2. Property Controlling T R SECTION in Section T R 3. Miscellaneous Т Property in Sec. Register of Deeds Stamp & File Number 1 , Recorded Plat 2 5. Private Claims 3 Oct. I. James E. Evans , in a field survey on 4 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points 5 mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, 6 Bureau of Land Management or by a decree of a Court of Law and for that the corner points 7 mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, 8 recovered, found as expressed below: 9 10 NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate. 12 A. Description of original monument and accessories and/or subsequent restoration: I-11 SECTION CORNER COMMON TO SECTIONS 26, 27, 34 and 35 T39N - R10W N77°E GLO: Set post FIR 15 lks. (9.90') HEMLOCK 8" \$41°W 18 lks (11.88') Sept 1845 By John Burt DS 8-12-58 - Mary C. Feindt RLS #3920 Set concrete monument as shown in the plat of "BEAVER HARBOR" Liber 2 Pg.56 No witnesses. 2-05-76 - Lawrence R. Feindt PS #21566 Found concrete monument LCRC Liber 2 Pg 37 12" Hemlock East 12.00' 12" Hemlock S60°W 18.25' 11" Hemlock N45°W 39.25' 7-07-78 - L. R. Feindt, Found concrete monument for survey for Walker Hill Same witnesses. 12-13-78-Sherman A. Chamberlain PS #25834 Found concrete monument and used in survey for Donald Hogan Same witnesses. 6-24-81 - John E. Ferguson used concrete monument for survey for Edward Palmer Same witnesses. 12-8-89 - George J. Avendt Jr. PS # 16034 Used concrete monument in survey for Wojan Construction Co. Same witnesses. 7-31-92 - Mary C. Feindt Used concrete monument in survey for Bud Esch Same witnesses. 7-31-92 - Mary C. Feindt Used concrete monument in survey for Daniel Clark Same witnesses. Charlevoix Co. Surveyor B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: APPROVED I-11 SECTION CORNER COMMON TO SECTIONS 26, 27, 34 and 35 T39N - R10W Mary C. Ferm Signatura_ 16.199.9 FOUND CONCRETE MONUMENT ON PLAT LINE .. Date: Nec I-11 to H-11 GLO = 2640L. R. Feindt = 2640.10' J. E. Ferguson = 2639.60 Meas = 2639.54' C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: I-11 SECTION CORNER COMMON TO SECTIONS 26, 27, 34 and 35 T39N - R10W AND DE MICHOLINA FOUND CONCRETE MONUMENT AT END OF CLEARED BRUSH LINE AT THE END OF SUBDIVISION. 8" BIRCH N529E 21.67' SET NAIL & CAP #22431 IN NW SIDE 16* HEMLOCK \$85°E 12.17' SET NAIL & CAP #22431 IN SW SIDE (R=12.00') 20° HEMLOCK S60°W 18.67 SET NAIL & CAP #22431 IN SVY SIDE

AND IS ACCEPTED AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER NO. 22431

Date TAND Signed by

Surveyor's Michigan License No.

22431

4163 - 003 MAGE 281