

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Dickinson	Located In:	Corner Code #
(County)		
NORWAY TOWNSHIP		
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling Section	S 17 T 40N R 29W	15
	S 17 T 40N R 29W	16
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

8/06/2013AD
Jeremy J. Pipp, in a field survey on 8/06/2013AD do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(15) West One-Sixteenth corner common to Sections 17 and 20. Not set in original survey, no evidence of subsequent establishment.

(16) East One-Sixteenth corner common to Sections 17 and 20. Not set in original survey, no evidence of subsequent establishment.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(15) Corner position established mid-point and on-line between the South One-Quarter corner and the Southwest corner of Section 17.

(16) Corner position established mid-point and on-line between the South One-Quarter corner and the Southeast corner of Section 17. Found Squared Tree NE 1.5 feet.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(15) DNR monument
6" Ironwood N68E 17.78' (1/16S,BT)
10" W. Pine S31E 23.02' (1/16S,BT)
7" Cherry S58W 55.06' (1/16S,BT)
8" Cherry N34W 40.84' (1/16S,BT)

All trees are blazed, scribed, and painted. Measurements are to nail in side of tree, bearings are magnetic

(16) DNR monument
5" Cedar N54E 11.35' (1/16S,BT)
4" Cedar S64E 18.48' (1/16S,BT)
12" Cedar S09W 18.75' (1/16S,BT)
13" Cedar N49W 10.71' (1/16S,BT)

All trees are blazed, scribed, and painted. Measurements are to nail in side of tree, bearings are magnetic.

Signed by Jeremy J. Pipp
Surveyor's Michigan License No. 50447

For the Michigan Department of Natural Resources



Date August 26, 2013