LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

or corners in

Dickinson	_ Located In:	Corner Code #	
(County) 3REEN TOWNSHIP			
Public Land Survey	TR		
2. Property Controlling n Section	S 16 T 42N R 27W S 16 T 42N R 27W S T R	11 15	
3. Miscellaneous Property in Sec.	S T R S T R		Register of Deeds Stamp & File Number
4. Lot No. , Red	corded Plat		A B C D E F G H I J K L
5. Private Claims	•		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	12/18/201	2AD	2 - 6 5 4 3 2 1 -
, Jeremy J. Pipp , ii	n a field survey on 12/18/201	12AD do hereby state	3
	74, Michigan P.A. of 1970, the corner p		
above were in conformance with r			
nstructions of the United States I			
	orner points mentioned in lines 3, 4 and		
he rules of the Michigan Board e-established, monumented, recov	¹ , 8 19 20 21 22 23 24		
e established, monumented, recov	ered, found as expressed below:		9
NOTE: Not more than 2 corr	ners, all in the same town and range		10 30 29 28 27 26 25
	11		
on this certificate.			12 31 32 33 34 35 36
			13

- 4. Description of original monument and accessories and/or subsequent restoration:
- (11) Southwest One-Sixteenth corner of Section 16. Not set in original survey, no evidence of subsequent establishment.
- (15) West One-Sixteenth corner common to Sections 16 and 21. Not set in original survey, no evidence of subsequent establishment.
- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
- (11) Corner position established at the intersection of the South and West One-Sixteenth lines of Section 16.
- (15) Corner position established mid-point and on-line between the South One-Quarter corner and the Southwest corner of Section 16.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(11) DNR monument		(15)	DNR	monument					
4" Cedar	N66	27.47'	(1/16S,BT)	8" Maple		N51E	23.48'	(1/16S,BT)	
8" W. Birch	S51	31.73	(1/16S,BT)	13" Maple		S23E	36.80'	(1/16S,BT)	
8" Balsam	\$82	V 6.06'	(1/16S,BT)	10" Maple		S63W	20.66'	(1/16S,BT)	
4" Spruce	N35	W 9.54'	(1/16S,BT)	7" Maple		N56W	23.77'	(1/16S,BT)	
All trees are blazed, scribed, and			All treases	All treaspare blazed, scribed, and					
painted. Measurements are to nail in		painted? M	painted Measurements are to nail in						
side of tree, bearings are magnetic.			whe of tree	s de of tree, bear ngs are magnetic.					

Surveyor's Michigan License No.

PROFESSIONAL

July 18, 2013

Rervised Oct., 1995

For the Michigan Department of Natural Resources

20152

Signed by

REVISED BY MICHAEL STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971

Revised May 14, 1975

Revised Jan., 1983