LAND CORNER F For corners in Filing Requirement	RECORDATION CERTIFICATE ent of Act 74, Mich. P.A. 1970
	RECORDED
<u>Dickinson</u> Located In: Corner C Sagola Twp.	1999 NOV 29 M 10: 31
1. Public Land Survey T 42NR 30W T R T R T R T R T R 2. Property Controlling S T R in Section S T R 3. Miscellaneous S T R	REGISTION REGISTION
Property in Sec. STR	Register of Deeds Stamp & File Number
4. Lot No, Recorded Plat	TICSNI
5. Private Claims	A B C D E F G H I J K L
I, <u>Robert F. Perkins</u> , in a field survey on <u>Sept. 10</u> , 19 requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned conformance with regulations and rules therefore as required in the current mai United States Department of the Interior, Bureau of Land Management or by a that the corner points mentioned in lines 3, 4 and 5 above were in conformance Board of Land Surveyors or by a Decree of a Court of Law; established recovered, found as expressed below:	nual of survey instructions of the decree of a Court of Law and /or
NOTE: Not more than 2 corners, all in the same town and range, may on this certificate.	- - - - - - - - - -
	12 31 32 33 34 35 36
A. Description of original monument and accessories and/or subseq L-3 ½ Corner 12 John Burt, D.S. 1850 Set ½ Post Original Bearing Trees Spruce 10" N68°E 38 Lks. Spruce 16" S54°W 47 Lks. B. Description of corner evidence found and/or method applied in rectal corner.	K-4 2 Corner 11/12 John Burt, D.S. 1850 Set Spruce 2 Post Tamarack 12" S77°E 8 Lks. Cedar 16" N81°W FT6D Lks THE DICKINSON COUNTY CHAPLET PLUE GROUP AS THE OFFICIAL GORGLE ULDER MICHIGAN PUBLIC ACT 365 OF 1890 AT A MEETING HELD ON
or Accessories Found. Established Corner Location by Single Proportionate Method from Section Corner 2 Mile East and 2 Mile West.	or Accessories Found. Found K.C. Corp. Pipe Marker with Brass Cap as estblished by Neal Sperhake, RLS on 6-2-1962. from G.L.O. Bearing Tree. 1960 Bearing Trees Cedar 6" S78°E 30 Lks. Cedar 6" N76°W 65 Lks. Old Report #450
C. Description of monument for corner and accessories established to	perpetuate locating the position of the corner
L-3 Set 3½" Stamped Cap D.C. Remon. Marker New Witnesses Fir 4" N27°W(M.B.) 21.44' Nail/Tag Fir 7" N65°E(M.B.) 58.35' Nail/Tag Fir 12" S20°E(M.B.) 16.95' Nail/Tag Spruce 14" S45°W(M.B.) 26.06' Nail/Tag Placed carsonite Marker 1.0' North	K-4 Accepted Marker described in "B" above. New Witnesses Cedar 8" N15°W(M.B.) 20.81' Nail/Tag Cedar 8" N20°E(M.B.) 14.20' Nail/Tag Cedar 5" S55°W(M.B.) 16.35' Nail/Tag Cedar 10" S75°E(M.B.) 19.55' Nail/Tag Placed Carsonite Marker 1.0' South
Signed by Count of English Surveyor's Michigan License No. 12027	Date Nov. 5, 1999
Liber 2	FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971 REVISED MAY 14,1975 REVISED JAN., 1983 REVISED OCT., 1995

PARI= 471