

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Form with fields for Dickinson (County), Located In, Corner Code #, and sections 1-5 for Public Land Survey, Property Controlling in Section, Miscellaneous Property in Sec., Lot No., and Private Claims.

Register of Deeds Stamp & File Number

Table with 13 rows and 13 columns (A-M) for recording deed stamps and file numbers.

I, Jeremy J. Pipp, in a field survey on 8/20/2012AD do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- (11) Southwest One-Sixteenth corner of Section 21. Not set in original survey, no evidence of subsequent establishment.
(01) West One-Sixteenth corner common to Sections 24 and 25. Not set in original survey, no evidence of subsequent establishment.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- (11) Corner position established at the intersection of the South and West One-Sixteenth lines of Section 21.
(01) Corner position established mid-point and on-line between the North One-Quarter corner and the Northwest corner of Section 25.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- (11) DNR monument: 12" Tamarack N46E 19.42' (1/16S,BT), 7" Cedar S37E 17.94' (1/16S,BT), 7" Cedar S51W 20.12' (1/16S,BT), 6" Cedar N51W 22.33' (1/16S,BT). All trees are blazed, scribed, and painted. Measurements are to nail in side of tree, bearings are magnetic.
(01) DNR monument: 14" Cedar N45E 54.35' (1/16S,BT), 16" Tamarack S28E 28.44' (1/16S,BT), 10" Cedar S88W 44.14' (1/16S,BT), 10" Tw. Tmrk. N22W 6.78' (1/16S,BT). All trees are blazed, scribed, and painted. Measurements are to nail in side of tree, bearings are magnetic.

Signed by [Signature] Surveyor's Michigan License No. 50447 For the Michigan Department of Natural Resources, Office of Land and Facilities, August 29, 2012

