

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Dickinson

(County)

Located in:

Corner Code #

1. Public Land Survey

T 43N R 28W
T 43N R 28W

E1

G1

2. Property Controlling
in Section

S T R
S T R

3. Miscellaneous
Property in Sec.

S T R
S T R

4. Lot No. , Recorded Plat

5. Private Claims

G1 Apr 16 1998

E1 Apr 21 1998

I, Stephan J. Szyszkoski, in a field survey on _____, 19____ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:
(E1) Corner common to Sections 4-5 T43N-R28W and Sections 32-33 T44N-R28W. Corner reestablished in 1969 and recorded in 1970 by A.O. Enger. Corner monument 1" I.D. iron pipe with 4" aluminum cap. Witnesses to Corner: Sugar Maple 7 S43E 59.5 links, Sugar Maple 6 N33 1/2E 50.5 links, Sugar Maple 5 N38 1/2W 42.5 links, Basswood 8 S80W 76 links.
(G1) Corner common to Sections 3-4 T43N-R28W and Sections 33-34 T44N-R28W. Jan. 27, 1972 record by A.O. Enger states "October 16, 1969: Corner reestablished by proportionate measurement on line between original section corner 1, 2, 35, and 36, T43-44N, R28W and original township corner T43-44N, R28-29W. Corner monument 1" I.D. x 3/8" iron pipe with 4" aluminum cap. Witnesses to corner, Sugar Maple 10 S63E 27.5 links, Sugar Maple 8 N70E 64 links, Sugar Maple 12 S22W 45 links, Sugar Maple 6 N55W 29 links".

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(E1) Recovered the 1969 monument as described, in good condition, and at record bearing and distance from the three Sugar NBTs, all recovered in good condition with blazes overgrown. Left the monument in place and marked one new accessory as described below. Corner recovered and re-witnessed by B. Wheeler and D. Lampela, Baraga District Office.
(G1) Recovered the 1969 monument as described and in good condition. Determined that the 1969 Enger survey was erroneous as the result of a measurement error made between E1 and K1. I rejected the monument as representing the position of the corner and I reestablished the corner by single proportionate measurement to the original record between reestablished section corners 5286.80' West and 10,573.58' East, from which the 1969 monument was found 9.00' Westerly. I removed the 1969 monument and placed it at the position for the corner. Corner placed and witnessed by D. Lampela and B. Wheeler, Baraga District Office.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(E1) Found 1" pipe with 4" State of Michigan tablet. The 1969 witnesses:

8" Sugar N37E 33.2' in clump of 3

15" Sugar S40E 38.9'

8" Sugar N35W 28.0'

Blazed and scribed the following:

12" Sugar S17W 25.3' "S5 NBT"

Bearings are magnetic. Placed a squared post adjacent.

(G1) 1" pipe with 4" aluminum cap.

Blazed and scribed the following:

8" Sugar N67E 34.15' "S34 NBT"

12" Y. Birch N89E 14.65' "S34 NBT"


13" Sugar S45E 9.85' "S3 NBT"

18" Sugar S37W 32.7' "S4 NBT"

8" Sugar N63W 27.6' "S33 NBT"

Placed squared cedar post adjacent.

Bearings are magnetic.



Signed by

Stephan J. Szyszkoski

Date

6/25/98

Surveyor's Michigan License No.

33986

For the Michigan Department of Natural Resources - Forest Management Division