

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

DICKINSON COUNTY

FOR CORNERS OF --:	LOCATED IN --:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 43 ^{N.} XX R. 29 ^{E.} XX W.	C5, C4, C3
2. PROPERTY CONTROLLING IN SECTION 17	T. 43 ^{N.} XX R. 29 ^{E.} XX W.	2
3. MISCELLANEOUS PROPERTY IN SECTION	T. S. R. E. W.	
4. LOT NO.	RECORDED PLAT	
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on See Below, 19 , established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on , 19 , found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner C5: Original monument and accessories not found.

Corner C4: Original monument and accessories not found.

Corner C3: Original monument and accessories not found.

Corner 2: Not set on original survey nor subsequently apparently.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner C5: Restored 5-7-81 by double proportion distance.

Corner C4: Restored 5-11-81 midway and on line between section corners north and south.

Corner C3: Restored 5-7-81 by double proportion distance.

Corner 2: Established 5-14-81 midway on line between corners east and west.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner C5: Set 1" I.D.x32" iron pipe with 4" alum. cap.	Corner 2: Set 1" I.D.x32" iron pipe with 4" alum. cap.
9" White Birch N55°E 22.9 ft. S8,NBT	6" Sugar S70°W 21.6 ft. 1/16S,BT
8" Maple N73°W 39.0 ft. S7,NBT	5" Sugar S50°E 23.7 ft. 1/16S,BT
24" Red Pine S20°W 17.2 ft. S18,NBT	6" Sugar N77°E 8.7 ft. 1/16S,BT
Corner C4: Set 1" I.D.x32" iron pipe with 4" alum. cap.	
6" Spruce S34°E 3.5 ft. 1/8S,NBT	
4" Spruce S52°W 4.5 ft. 1/8S,NBT	
2" Spruce S85°W 3.5 ft. Squared Marked 1/4 7 and 8	
Corner C3: Set 1" I.D.x32" iron pipe with 4" alum. cap.	
6" Red pine N61°N 23.1 ft. S6,NBT	
5" Red Pine S42°W 34.4 ft. S7,NBT	
5" Red Pine N72°E 93.7 ft. S5,NBT	

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

(SEAL)


FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett DATE 10-22-81

CHIEF OF SURVEY PARTY
MICHIGAN REGISTERED LAND SURVEYOR
Keith L. Sackett
Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006



FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET