LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

for corners in

Dickinson	Located In:	Corner Code #					
(County) VEST BRANCH TOWNSHIP I. Public Land Survey	TR						
2. Property Controlling n Section	T R S 20 T 44N R 27W S 20 T 44N R 27W S T R	05 15					
3. Miscellaneous Property in Sec.	S T R R		Registe	r of Deeds Sta	amn & Fil	la Numb	or
4. Lot No. Red 5. Private Claims	corded Plat		A B C	D E F	3 H I	J K	LM
	9/24/20	13AD	2 6	╼╪╼┼╾┋╼	┝╬┼		
, Jeremy J. Pipp , ir	a field survey on 9/25/20	13AD do hereby state	3	1			+
·	74, Michigan P.A. of 1970, the corner		4 7	- 8 9	10-	-11	—1 <u>2</u> —
above were in conformance with r	regulations and rules therefore as requi	ired in the current manual of survey	5				_
	Department of the Interior, Bureau of	•		-1716	15-	-14-	—13—
	orner points mentioned in lines 3, 4 and of Land Surveyors or by a Decree			•			
re-established, monumented, recov	i ii	_2021	722	-23 	—24 		
	•		9 30				
NOTE: Not more than 2 corners, all in the same town and range, may be recorded			10 -30	_2928		-26-	—25—

on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- (05) Center-North One-Sixteenth corner of Section 20. Not set in original survey, no evidence of subsequent establishment.
- (15) West One-Sixteenth corner common to Sections 20 and 29. Not set in original survey, no evidence of subsequent establishment.
- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
- (05) Corner position established mid-point and on-line between the Center One-Quarter corner and the North One-Quarter corner of Section 20.
- (15) Corner position established mid-point and on-line between the South One-Quarter corner and the Southwest corner of Section 20.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(05) DNI	R monument	(15) DNR	monument			
4" Ironwood	N56E 27.61' (1/16S,BT)	6" Cherry	NO7E 53.68' (1/16S,BT)			
8" Maple	S53E 30.88' (1/16S,BT)	10" Balsam	\$17E 10.69' (1/16S,BT)			
10" Maple	\$62W 21.15' (1/16\$,BT)	11" Spruce	\$39W 39.15' (1/16S,BT)			
13" Maple	N10W 20.56' (1/16S,BT)	6" Spruce	N75W 65.26' (1/16S,BT)			
All trees are	blazed, scribed, and	All trees are d	azed, scribed, and			
painted. Measurements are to nail in			ents are to nail in			
side of tree, bearings are magnetic.		side of tree, bearings are magnetic. JEREMY J.				
		JEREMY	J. 1			

Surveyor's Michigan License No.

October 1, 2013

TE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971

For the Michigan Department of Natural Resources

Signed by