

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Dickinson	Located In:	Corner Code #
(County)		
1. Public Land Survey	T 44N R 29W	L2
	T R	
	T R	
2. Property Controlling	S T R	
in Section	S 1 T 44N R 29W	14
	S T R	
3. Miscellaneous	S T R	
Property in Sec.	S T R	

Register of Deeds Stamp & File
Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims

Jul 28 2005

I, Stephan J. Szyszkoski, in a field survey on _____, 20____ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(L2) Center of Section 1. Not established in the original survey.
(14-Sec. 1) South 1/16 corner between Section 1 T44N-R29W and Section 6 T44N-R28W. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(L2) Established the corner at the intersection of straight lines connecting opposite Quarter corners.
(14-Sec. 1) Established the corner midway and on a straight line between Section corner 1310.20' South and Quarter corner 1310.20' North.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(L2) Set 1"IDx32" I.pipe with 4" alum.	(14) Set 1"IDx32" I.pipe with 4" alum.
MDNR cap. Set measuring nails in:	MDNR cap. Set measuring nails in:
7" Maple N17E 110.6' mrkd "C1/4 BT"	5" R.Pine N03E 32.2' mrkd "1/16S BT"
7" Poplar N68E 57.3' do	12" dbl Oak S24E 61.4' do
8" Spruce S46W 67.6' do	10" dbl Oak S06W 19.3' do
5" Spruce S82W 24.3' do	7" Maple S82W 8.3' do
Set sq'd cedar post adjacent. Bearings are magnetic. Distances are to nail with tag.	Set sq'd cedar post adjacent. Bearings are magnetic. Distances are to nail with tag.



Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 9/29/05

For the Michigan Department of Natural Resources, Office of Land and Facilities