

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Dickinson

(County)

Located In:

Corner Code #

1. Public Land Survey

T R

T R

T R

S T R

2. Property Controlling
in Section

S

S 1

S 1

T 44N R 29W

T 44N R 29W

9

15

3. Miscellaneous
Property in Sec.

S

S

T R

T R

4. Lot No. , Recorded Plat

5. Private Claims

Aug 01 2005

I, Stephan J. Szyszkoski, in a field survey on _____, 20____ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(9-Sec. 1) East 1/16 corner, Section 1. Not established in the original survey.

(15-Sec. 1) West 1/16 corner between Sections 1 & 12. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(9-Sec. 1) Established the corner midway and on a straight line between Quarter corner 1305.20' East and Center of Section 1305.20' West.

(15-Sec. 1) Established the corner midway and on the section line between Section corner 1324.00' West and Quarter corner 1324.00' East.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner.

(9) Set 1"IDx32" I.pipe with 4" alum.

MDNR cap. Set measuring nails in:

5" Maple S88E 21.8' mrkd "1/16S BT"

4" Maple S66E 11.2' do

6" Spruce S55W 36.7' do

8" J.Pine N87W 14.1' do

Set sq'd cedar post adjacent. Bearings are magnetic. Distances are to nail with tag.

(15) Set 1"IDx32" I.pipe with 4" alum.

MDNR cap. Set measuring nails in:

12" R.Pine N02E 58.2' mrkd "1/16S BT"

8" J.Pine N46E 32.0' do

8" W.Pine S39E 29.8' do

8" twin Oaks S10E 48.9' do

Set sq'd spruce post adjacent. Bearings are magnetic. Distances are to nail with tag.



Signed by

Stephan J. Szyszkoski

Date

9/29/05

Surveyor's Michigan License No.

33986

For the Michigan Department of Natural Resources, Office of Land and Facilities