

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Emmet
(County)

Located In

Corner Code #

1. Public Land Survey	T	36 N	R	5 W	K-7
	T		R		
2. Property Controlling in Section	S	23	T	36 N	R
	S		T	5 W	7
3. Miscellaneous Property in Section	S		T		R
	S		T		R

Register of Deeds Stamp & File Number

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on December 20, 2006 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

K-7 GLO 1840 John Mullett set post for corners 13,14,23 & 24.

Wit: 13" Beech S37°E 16 Links
6" Beech S45°W 10 Links

7- This corner position was not established during the original government survey.

1984 Liber 2, Page 114, Michael Trowbridge RLS #27463 found ¾" pipe for corner.

Wit: 5" Red Pine N38°W 44.14'
8" Maple S10°E 33.86'

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

K-7 Found a ¾" pipe fitting M. Trowbridge's survey in section 24.

7- Established the Northeast corner of the Southeast quarter of the Northeast Quarter of section 23 per B.L.M. instructions for the subdivision of a section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-7 Added P.S. cap #33981 to Fd. ¾" pipe

7- Set 5/8" x 32" rerod with PS cap #33981

Wit: 4" Maple S14°E 37.06'
8" Cherry S55°W 44.54'
9" Red Pine N57°W 135.81'
14" Red Pine N62°E 64.95'

Wit: 14" Red Pine N72°W 27.65'
14" Red Pine S52°W 34.04'
5" Elm S50°E 29.13'
8" Elm N85°E 25.10'
Carsonite post West 33.00'

Signed by:

Carl T. Kiiskila

Date:

2-6-07

Surveyor's Michigan License No.:

33981

