

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Emmet
(County)

Located In

Corner Code #

1. Public Land Survey	T	36N	R	4W	C-7
	T	36N	R	4W	C-8
2. Property Controlling in Section	S	T		R	
	S	T		R	
3. Miscellaneous Property in Section	S	T		R	
	S	T		R	

4. Lot No: _____ Recorded Plat: _____

5. Private Claims: _____

I, Carl T. Kiiskila, in a field survey on June 25, 2008 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

C-7 GLO-1840-John Mullett- Set Post Corner Secs.
17,18,19,20.
Wit: Beech 18" S21°W 22 links
Beech 8" N25°E 7 links

C-8 GLO-1840-John Mullett- Set Qr. Section Post.
Wit: Sugar 30" S46°W 7 links
Sugar 30" S30°E 12 links

Certificate of Survey-L.1,p.292-1978-John Ferguson
P.S.#24595- Set ¾" pipe from longtime resident
testimony.
Wit: 8" Poplar N85°W 21.5'
4" Maple N30°E 22.02'
15" Maple S63°E 22.65'
6" Pine S17°E 64.2'

L.C.R.C.-L.1,p.292-1978-John Ferguson
P.S.#24595- Set ¾" pipe online between NE & SE
corners of section on old fence line West.
Wit: 5" Basswood N45°W 31.45'
8" Basswood N30°E 34.8'
6" Pine S88°E 27.91'

L.C.R.C.-L.2,p.137-1985- Michael Trowbridge
P.S.#27463- Fd. 1" pipe in "T" road intersection.
Wit: 8" Aspen N85°W 21.86'
20" Maple S58°E 23.17'
5" Maple N36°E 22.28'

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

C-7 Found ½" rod with P.S. cap# 27463

C-8 Found ½" iron rod 3' east of C/L N-S road on old
fence line west.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-7 ½" rod with P.S. cap# 27463
Wit: S70°W 39.28' to found N&T "27463 MAT" SE side
8" Aspen
N49°W 35.37' to found N&T "27463 MAT" SW side
7" Aspen
S48°E 46.22' to found N&T "27463 MAT" SW side
8" Elm
S52°E 56.65' to found N&T "27463 MAT" SW side
24" Maple
Set Carsonite post West 25'±

C-8 Added P.S. Cap# 33981 to found ½" iron bar
Wit: S73°W 46.97' to set N&T S side 10" Elm
N47°W 37.90' to set N&T NE side 10" Cherry
N36°W 60.99' to found nail on NE side 10" Basswood
N31°E 78.24' to found nail "R.C. Dunn" cap on SE
side of P. Pole
Set Carsonite Post West 33'±

Signed by:

Carl T. Kiiskila

Date:

7-20-09

Surveyor's Michigan License No.:

33981

