

SURVEY & REMONUMENTATION

NOV 12 1997

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Gogebic
(County)

Located In:

Corner Code #

1. Public Land Survey

T 43N R 38W

F-5

2. Property Controlling
in Section

S T R
S T R

3. Miscellaneous
Property in Sec.

S T R
S T R

4. Lot No. , Recorded Plat

5. Private Claims

Quarter Corner Section 9 & 16, T43N, R38W

I, Gary L. Pisoni, in a field survey on June 26, 19 97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by Zelotes B. Searls, U.S. Deputy Surveyor on July 30, 1851.

Original corner: Wood post

Original bearing trees:

Sugar	10"	S 47°E	26 links (17.16 feet)
Hemlock	16"	N 50°W	1 link (0.66 feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Original corner wood post not found.

Found the remains of a hemlock stump rotted at ground line and located on the edge of a side hill.
Found a row of hemlock knots on either side of the former hemlock trunk, along the side hill.

No evidence of Sugar B.T. found.

GLO distance checks good East and West from the Northeast corner of Section 16 to the Closing Corner between Sections 9 and 16 on the Michigan/Wisconsin State boundary line.

Accept the remains of the hemlock as the original bearing tree and set the quarter corner position at record bearing and distance from the remains of the original hemlock B.T.

Corner Record Research on file with County Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position, I set a 2" diameter by 30" long split base aluminum pipe monument with a 3" cast aluminum cap, stamped to read: County Remonumentation, T43N, R38W, 1/4., S-9, S-16, 1997, RLS-27457 from which I established the following new blazed and scribed bearing trees: (all measurements taken to a nail in side of tree)

Sugar Maple	11"	N 07°E	7.74 feet
Sugar Maple	7"	S 69°E	22.36 feet
Sugar Maple	7"	S 30°W	2.21 feet
Sugar Maple	9"	N 84°W	24.20 feet
Steel sign post		N 10°W	0.57 feet

97-03

Signed by Gary L. Pisoni

Date 7-15-97

Surveyor's Michigan License No. 27457

Register's Office }
Gogebic County } ss.

Received for record the
27TH day of OCTOBER
A. D. 1997 at 11:15 o'clock
A. m., and recorded in
Liber 6 of CORNERS
on page 246.
Rimona Collins, Deputy
Register of Deeds

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

PEER GROUP APPROVED

Richard P. Deahn 10/8/97
COUNTY REPRESENTATIVE

