

SURVEY & REMONUMENTATION

SEP 08 1998

SECTION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office }
Gogebic County } ss.

Received for record the
17th day of MARCH

A. D. 1998 at 9:50 o'clock
A m., and recorded in

Liber 6 of CORNERS
on page 318

Ramona Collins Deputy
Register of Deeds

Register of Deeds Stamp & File Number

For corners in

Gogebic
(County)

Located In:

Corner Code #

- | | | |
|-------------------------|-------------|-----|
| 1. Public Land Survey | T 44N R 39W | E-3 |
| | T R | |
| | T R | |
| | T R | |
| 2. Property Controlling | S T R | |
| in Section | S T R | |
| 3. Miscellaneous | S T R | |
| Property in Sec. | S T R | |

4. Lot No. , Recorded Plat
5. Private Claims

Section Corner 4, 5, 8 & 9; T.44 N., R.39 W.

I, Richard L. Drahn in a field survey on December 10, 1997, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by Wells Burt on 9/1/1851. Original B.T.s --- Lynn 10" S.85 E. 8 links (5.28') --- Fir 8" N.48 W. 15 links (9.90') ---

1939 MSHD field notes show this corner marked with a cedar stake and B.T.s

10" Maple	N.09 E.	13.78'
9" Maple	N.54 E.	10.57'
8" Maple	S.24 E.	15.06'

Donald D. Lappala (12585), on 5/14/59 recovered the cedar stake and B.T. at N.54 E. 10.57'.

Corner monumented on 7/10/85 by Richard L. Drahn (21564) from the remains of the 1939 B.T.s, natural feature ties, a line tree and distances to corners

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

north, south, east and west. He set a 2" X 30" alum. pipe with a 3 1/4" stamped alum. cap and the following new B.T.s:

9" Sugar Maple	N.08 E.	17.44'
14" Sugar Maple	S.24 E.	15.45'
9" Sugar Maple	S.71 W.	21.97'
6' Steel sign rail	N.88 W.	2.65'

Corner recorded in Gogebic County in Liber 2, Page 739 on 3/25/86.

Corner research on file with Gogebic County records.

Recovered Drahn's monument as described and his B.T.s as follows:

11" Sugar Maple	N.08 E.	17.47'
17" Sugar Maple	S.22 E.	15.90'
12" Sugar Maple	S.70 W.	21.98'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

6' Steel sign rail	N.88 W.	2.64'
--------------------	---------	-------

No evidence of the original B.T.s recovered.

New bearing tree referenced:

9" Sugar Maple	N.54 E.	6.30'
----------------	---------	-------

PEER GROUP APPROVED

Richard L. Drahn 12/19/97
GOGEBIC RE-MONUMENTATION

Signed by Richard L. Drahn

Date December 12, 1997

Surveyor's Michigan License No. 21564

USFS E-9

318

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5		4	3		2	1				
3												
4	7	8		9	10		11	12				
5												
6	18	17		16	15		14	13				
7												
8	19	20		21	22		23	24				
9												
10	30	29		28	27		26	25				
11												
12	31	32		33	34		35	36				
13												

