LAND CORNER	RECORDATION	CERTIFICATE
Filing Requirem	ont of Act 74 st	liah D.A. 1070

Register's Office

LAND CORNER RECORDATION CERTIFICATE					- acense contifi					
For corners in Filing Requirement of Act 74, Mich. P.A. 1970			970	O Received for record the						
Gogeb <b>ic</b>	Located In:	Corner Code -44		11 77		of_A				
(County)	Confer Code .77									
Public Land Survey	45N 40W A-1.1			A. D. 19 93 at 9:15 o'clock  A. m., and recorded in						
i. Public Land Survey	T P	001	Ták							
	T R	081		er <u>4</u>		ے ۔ اہ۔	ORN	ries		
	T 46NR 40W	ONT. COUNTY		page	<del>244</del>					
2. Property Controlling	S T R		<u> 1</u> 2	etty	Sug	<u>و سه</u>	Dep	uly		
in Section	S T R			o	Ke	gister	of Ote	Osb:		
3. Miscellaneous	\$ T R		Register o	f Deed	s Stam	n & File	. Numl	ber		
Property in Sec.	S R									
4. Lot No Re	ecorded Plat									
5. Private Claims			— A	ВС	) E F	G H	J	KLN		
@ 64.97 CHS.			2	 6			1 2-	!_		
Gy 67,7/ CAS.	4 E 3 C		3			41		1		
. Garv I. Pisoni	More		4	7		10-	11-	12_		
do hereby certify that under requ	in a field survey on Mar	f 1970, the corner points mentioned	. 5	4	1-1-		1			
in lines 1 and 2 above were in	conformance with regulations and	rules therefore as required in the	61	817		15	<del>    1</del> 4-	13		
current manual of survey instruc	ctions of the United States Departm	gent of the Interior Bureau of Land	7		+	+	<b>↓</b> _↓			
above were in conformance with	Journ of Law and/or that the corner the rules of the Michigan Board of	points mentioned in lines 3, 4 and 5 Land Surveyors or by a Decree of a	8	20	21-		23-	24		
Court of Law; established, <u>re</u>	-established, monumented, re-mo	onumented, recovered, found as	9				$\coprod$	$\perp \perp$		
expressed below:			103	)—————————————————————————————————————	28	27	26-	25		
NOTE: Not more than 4 co	rners, all in the same town and	I range, may be recorded	11		$\bot\bot$	1-1-	$\perp \perp$			
on this certificate.			123	32	33-	34—	35—	36		
A. Description of original m	onument and accessories and/	On Suborniant in it	13					$\bot$		
Original corner e	stablished by John Bu	rt, U.S. Deputy Surveyo	on Ju	ly 9,	1847					
Original bearing	12" Hemlock as corner	r tree								
Cedar		V 50°W 13 links	/O =0	e						
00001	0	N 50 W 13 links	(8.58	feet)						
Description of corner avia	topoo found and/or make at a co	and the second second								

or method applied in restoring or reestablishing corner:

No original corner evidence found. Corner restored by single proportionate measurement methods on line between the Northwest corner of Section 6, T45N, R40W and the East meander corner between Sections 32 and 5.

Description of monument for corner and accessories established to perpetuate locating the position of the corner: At the corner position, I set a standard 2" diameter by 30" long split base aluminum pipe monument with a 3" cast aluminum cap, stamped to read: T46N, R40W, \$-31, S-6, M.C., T45N, 1991, R.L.S. 27457; from which I established the following new blazed and

scribed bearing trees: (all measurements taken to a nail in side of tree) 15' from waters edge.

Hemlock 5'' S 81 E 11.56 feet

Hemlock 12'' S 10 E 16.05 feet

Hemlock 20'' N 73 W 35.30 feet

Steel sign post S 38 W 1.27 feet PISONI

PISONI SURVEYOR No. 27457

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND REVISED MAY 14, 1975 REVISED JAN., 1983

U.S.F.S. #A-1,2

Date \_