

SURVEY & REMONUMENTATION

JAN 22 1998

SECTION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Gogebic (County)

Located In:

Corner Code #

1. Public Land Survey T 45N R 41W. J-7
2. Property Controlling S T R
3. Miscellaneous S T R
- Property in Sec. S T R

4. Lot No. , Recorded Plat
5. Private Claims

1/4 Corner 14 & 23; T.45 N., R.41 W.

I, Richard L. Drahn in a field survey on December 13, 1997, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by A. Merryweather on 6/4/1852. Original B.T.s --- 30" Hemlock (no bearing given in notes) 28 links (18.48') --- 24" Hemlock S.05 E. 28 links (18.48') ---
Corner re-established by Gary L. Pisoni (27457) on 12/18/89 by single proportionate methods. He set a 2" X 30" aluminum pipe with a 3 1/4" stamped aluminum cap and the following new bearing trees:

6"	Red Maple	N.24 W.	8.52'
7"	Red Maple	N.77 E.	7.89'
6"	Red Maple	S.13 W.	11.29'
6'	Steel sign post	S.45 W.	0.85'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Corner recorded in Gogebic County Liber 4, Page 55 on 1/22/92.

Corner research on file with Gogebic County records.

Recovered the monument as described and the bearing trees as follows:

7"	Red Maple	N.24 W.	8.48'
8"	Red Maple	N.75 E.	7.87'
7"	Red Maple	S.12 W.	11.34'
6'	Steel sign rail	S.53 W.	0.82'

No evidence of the original B.T.s remain.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

New bearing tree referenced:

6"	Red Maple	N.86 W.	21.44'
----	-----------	---------	--------

PEER GROUP APPROVED
Richard L. Drahn 12/19/97
GOGEBIC COUNTY

Register's Office } ss.
Gogebic County }

Received for record the
22ND day of DECEMBER
A. D. 19 97 at 11:00 o'clock
A. m., and recorded in
Liber 6 of CORNERS
on page 293
Ramona Collins, Deputy
Register of Deeds

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2								
3	7	8	9	10	11	12							
4													
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													



Signed by Richard L. Drahn Date December 15, 1997

Surveyor's Michigan License No. 21564