

# SURVEY & REMONUMENTATION

AUG 08 1997

COMMISSION

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Gogebic  
(County)

Located In:

Corner Code ##

1. Public Land Survey

T 45N R 45W

C-4-5

T R

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Closing Corner, Secs. 7 & 8, on Mic.--Wis. State Line

I, Richard L. Drahn in a field survey on May 5, 19 97,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by Austin Burt on August 9, 1851. Original B.T.s ---  
Cedar 8" N.52 W. 11 links (7.26') --- Cedar 12" N.58 E. 32 links (21.12') ---

Corner restored on 11/13/84 by R. Drahn (21564 and J. Goss (23509) from the  
remains of the two original B.T.s. The Cedar at N.52 W. was still scribed.  
They set a 3/4" by 8" solid alum. rod with a 3/4" stamped alum. cap and the  
following new bearing objects: --- 8" (10") Cedar N.40 W. (N.41 W.) 13.69'  
(13.69') --- 5" Balsam (now dead) N.07E. (N.15 E.) 8.16' (8.12') --- 9"  
Cedar (now dead) S.14 E. (S.14 E.) 12.90' (12.84') --- 6' Steel rail North  
(re-located N.20 W.) 1.8' (1.0')

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Corner recorded in Gogebic County in Liber 2, Page 615-616, on 12/6/84.

Recovered the corner as described and the bearing objects as indicated in  
parentheses above. Both original bearing trees were recovered badly decayed  
with scribing no longer visible.

Research form on file with Gogebic County records.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

From the above described monument I established the following new B.T.s:

5" Black Spruce N.55 E. 15.49' ft.

9" Cedar S.16 W. 19.91 ft.

PEER GROUP APPROVED

Richard L. Drahn 5/12/97  
COUNTY REPRESENTATIVE



Signed by Richard L. Drahn

Date May 8, 1997

Surveyor's Michigan License No. 21564

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983

USFS HJ - 5

100

Register's Office }  
Gogebic County } ss.

Received for record the

13<sup>TH</sup> day of MAY

A. D. 19 97 at 5:55 o'clock

P m., and recorded in

Liber 6 of CORNERS

on page 106

Ramona Collins, Deputy  
Register of Deeds

Register of Deeds Stamp & File Number

