

SURVEY & REMONUMENTATION

NOV 12 1997

COMMISSION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office }
Gogebic County } ss.

For corners in

Gogebic
(County)

Located In:

Corner Code #

- | | | |
|-------------------------|---------------------------|------------|
| 1. Public Land Survey | T <u>45N</u> R <u>46W</u> | CD - 1-2 |
| | T _____ R _____ | |
| | T _____ R _____ | <u>012</u> |
| | T _____ R _____ | |
| 2. Property Controlling | S _____ T _____ R _____ | |
| in Section | S _____ T _____ R _____ | |
| 3. Miscellaneous | S _____ T _____ R _____ | |
| Property in Sec. | S _____ T _____ R _____ | |

Received for record the
9TH day of OCTOBER
A. D. 1997 at 10:50 o'clock
A m., and recorded in
Liber 6 of CORNERS
page 224
Ramona Collins Deputy
Register of Deeds

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

Mile Corner No. 1½, Mich. -- Wisc. State Line

I, Richard L. Drahn, in a field survey on September 24, 1997, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by William Burt in 1847. Original B.T.s --- Y. Birch 14" N.50 E. 54 links (35.64') --- Cedar 10" S.87 W. 15 links (9.90') ---

Corner re-established by proportionate methods by Earl Harrington in 1928 on a dependent re-survey of the State Line. He set a standard brass capped concrete monument and two new B.T.s --- Y. Birch 18" S.06-45 W. 13.9' --- Cedar 10" N.32-40 W. 35.3' ---

Daniel K. Pleoger (Wisc. No. S-1537) recovered the concrete monument and the remains of the 1928 B.T.s and established the following new B.T.s on 10/11/88:

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

--- 12" (15") Yellow Birch N.25 E. (N.25 E.) 11.33' (11.19') --- 10" Yellow Birch (11") S.59 E. (S.58 E.) 12.38' (12.23') --- 6" (6") Sugar Maple S.01 E. (S.02 E.) 21.75' (21.73') --- 12" (15") Hemlock N.88 W. (N.87 W.) 18.63' (18.61') ---

Recovered the 1928 standard brass capped concrete monument and the decayed remains of the two 1928 B.T.s. Recovered D. K. Pleogers B.T.s as described in parentheses above.

Research form on file with Gogebic County records.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

From the above described concrete monument I established the following new bearing object:

6" Steel sign rail N.20 E. 2.64'

PEER GROUP APPROVED

Richard L. Drahn 10/8/97
COUNTY REPRESENTATIVE



Signed by Richard L. Drahn Date September 29, 1997

Surveyor's Michigan License No. 21564