

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office }  
Gogebic County } ss.

For corners in

Gogebic  
(County)

Located In:

Corner Code #

1. Public Land Survey

T46 N R44 W.

E-3

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

**SURVEY &  
MONUMENTATION**

JAN 05 2001

**SECTION**

Received for record the  
26<sup>TH</sup> day of MAY  
A. D. 1900 at 10:40 o'clock  
A m., and recorded in  
Liber 7 of CORNERS  
as page 292  
*Chester Fugge*  
Dep. Register of Deeds

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

*Sec. Cor. 4, 5, 8 & 9; T. 46 N., R. 44 W.*

I, Richard L. Drahn, in a field survey on MARCH 7, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE:** Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by Austin Burt on 8/14/1851. Original bearing trees:

Y. Birch	12"	S.56° E.	49 links	(32.34')
Sugar	14"	N.70° W.	32 links	(21.12')

Corner restored by Richard L. Drahn, RLS 21564 on 5/4/83 from a series of recovered line trees, natural feature ties and retracement measurements to recovered corners. All evidence of the original bearing trees had been destroyed. He set a 2" X 30" aluminum pipe with a 3 1/4" stamped aluminum cap and the following new bearing trees:

Red Pine	5"	N.40° W.	33.32'
White Spruce	12"	S.43° E.	9.16'
Red Pine	3"	S.36° W.	30.76'
Steel sign rail	6'	N.29° E.	2.5'

Corner recorded in Gogebic County Liber 2, Page 549 on 1/26/84.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Corner research on file with Gogebic County records.

Recovered the monument as described and the bearing trees as follows:

Red Pine	12"	N.45° W.	33.28'	(new nail)
White Spruce	17"	S.41° E.	8.93'	(new nail)
Red Pine	10"	S.35° W.	30.81'	(New nail)
Steel sign rail	6'	N.28° E.	2.48'	

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

New bearing tree referenced:

Black Cherry	10"	N.32° E.	10.00'
--------------	-----	----------	--------

**FIELD GROUP APPROVED**

*Richard L. Drahn* 05/24/00  
COUNTY REPRESENTATIVE

Signed by Richard L. Drahn Date April 30, 2000

Surveyor's Michigan License No. 21564



FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1976  
REVISED JAN., 1983  
REVISED OCT., 1995

USFS E-9