

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Gogebic
(County)

Located In:

Corner Code #

1. Public Land Survey

T46NR44W

I-10

T R

T R

T R

S T R

S T R

S T R

2. Property Controlling
in Section

3. Miscellaneous
Property in Sec.

**SURVEY &
REMONUMENTATION**

JAN 05 2001

SECTION

Register's Office
Gogebic County

Received for record the

26TH day of MAY

A. D. 1900 at 11:00 o'clock

A m., and recorded in

Liber 7 of CORNERS

Page 316

Cheryl Ruppe
Dep. Register of Deeds

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

Quarter corner, Sections 26 & 27, T46N, R44W

I, John P. Goss, in a field survey on March 6, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by Austin Burt, in 1851.

Original bearing trees: Hemlock 24" East 14 links (9.24')
Hemlock 12" N45°W 5 links (3.3')

Donald D. Lappala, 12585, on October 20, 1967, found wood post at record bearing and distance from one of the original bearing tree. He set a 2" I.D. iron pipe with 3" bronze tablet, to indicated the corner position; He established the following reference objects: 5" W. Pine - N 15° E - 9.8 ft.; 4" Spruce - S 66° 29.5 ft.; 4" Cedar - S 04° W - 11.0 ft. He recorded said corner in Liber T-17 USFS book on June 6, 1968 in Register of Deeds office.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found Donal D. Lappala, monument and accessories.

Act 74 research on file.

FIELD GROUP APPROVED

Richard R. Drach 05/24/00
COUNTY SUPERVISOR

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
From found monument and cap that reads: T.46 N., R.44 W., 1/4; S-26, S-27; R.L.S. 12585; 1967; I established the following new and existing reference objects:

14" White Pine	N 15° E	10.05 ft.
8" Spruce	S 66° E	29.46 ft.
7" Cedar	S 04° W	11.16 ft.
4"x4" Cedar post & sign	N 56° E	2.6 ft. to face
6" metal rail & sign	N 48° W	1.34 ft. to face
(All measurement taken to nail in side of tree)		



Signed by John P. Goss

Surveyor's Michigan License No. 23509

USFS # T-17

Date March 7, 2000