

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office
Gogebic County

Received for record the

22ND day of JUNE

A. D. 19 at 1:20 o'clock

P m., and recorded in

Book 7 of COPIERS

on page 392

Cheryl Ruppel, Dep.
Register of Deeds

For corners in

Gogebic
(County)

Located In:

Corner Code #

1. Public Land Survey

T46 N R46 W.

C-12

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

**SURVEY &
MONUMENTATION**

JAN 05 2001

Register of Deeds Stamp & File Number

SECTION

4. Lot No. , Recorded Plat

5. Private Claims

Quarter Corner 31 & 32; T.46 N., R.46 W.

I, Richard L. Drahn, in a field survey on May 31, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4			3		2		1	
3													
4	7		8		9			10		11		12	
5													
6	10		17		16			15		14		13	
7													
8	19		20		21			22		23		24	
9													
10	30		29		28			27		26		25	
11													
12	31		32		33			34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by Austin Burt on 6/23/1851. Original bearing trees:

Y. Birch	12"	S.81° E.	22 links	(14.52')
Y. Birch	10'	N.86° W.	21 links	(13.86')

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I restored the corner position at record bearing and distance from the remains of the two original bearing trees. The first is a large windthrown depression. The second one is now a 16-20" Yellow Birch stump, decayed to ground line. The 1.50 chain distance north from corner to "Enter swamp, E-W" agrees with the original field notes within 8 feet.

A 1" X 4.8' Iron pipe set by the Gogebic County Forestry dept. Bears N.86° W., 30.5' from the original corner location.

Corner research on file with Gogebic County records.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a 2" x 30" aluminum pipe monument with a 3 1/4" stamped aluminum cap and the following new B.T.s (all measurements taken to a nail in side of tree):

Red Maple	7"	N.63° W.	16.18'
Yellow Birch	11"	N.61° E.	25.94'
Red Maple	8"	S.01° E.	33.37'
Steel sign rail	6'	S.59° E.	2.61'

PEER GROUP APPROVED

Richard L. Drahn 6/2/00
COUNTY REPRESENTATIVE



Signed by Richard L. Drahn Date June 14, 2000

Surveyor's Michigan License No. 21564

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971

REVISED MAY 14, 1975

REVISED JAN., 1983

REVISED OCT., 1995

USFS X-5