SURVEY & REMONUMENTATION

OCT () 3 1996

COMMISSION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

ΓŲ	Comers in	
	Gogebic	Located In: Corner Code ##
1.	(County) Public Land Survey	1 47NR 44W. A-7
	·	T R T 47N R 45W. M-7
2.	Property Controlling in Section	S T R
3.	Miscellaneous Property in Sec	S T R

Register's Office ss. Gogebic County
Gogebic County 5
Received for record the
10th day of Juna
A D 19 96 at 10:00 o'clock
A m and recorded in
Liber 5 of CORNES
364
Remona Collins Deputy Register of Deeds
Kegister of Descir

Register of Deeds Stamp & File Number


4. Lot No. ___ . Recorded Plat _

5. Private Claims __

Sec. Cor. 18, 19, 13 & 24; T.47 N., R.44-45 W.

Richard L. Drahn in a field survey on May 21, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Lawland/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.



A. Description of original monument and accessories and/or subsequent restoration:

Corner established by Austin Burt on August 31, 1847. Original B.T.s ---Cedar 14" S.82 E. 28 links (18.48') --- Spruce 14" N.24 W 14 links (9.24') --- Fir 10" N.25 E. 25 links (16.50') --- Cedar 14" S.08 E. 30 liks (19.80'). Corner restored by Donald D. Lappala, RLS 12585 on 10/15/70 from the stump remains of the four original bearing trees and a natural feature tie south. He set a $2\frac{1}{2}$ " iron pipe with a 3" stamped brass cap and the following new bearing trees: --- 14" (17" Cedar N.21 W. (N.21 W.) 18.8' (18.51') --- 14" (16") White Spruce N.55 E. (N.57 E.) 28.7' (28.41') --- 3' Elm (now dead and down) S.60 E. 13.7'.

Corner recorded in Gogebic County in USFS Liber, Page N-1 on 8/10/70. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Act 74 research form on file with Gogebic County records.

Recovered the monument as described and the bearing objects as noted in parentheses above. A stump hole from the Fir bearing tree is all that remains of the original bearing trees.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Bearing objects referenced:

6' Steel sign rail S.25 E.

6' Steel sign rail West

4" X 4" Cedar post N.26 W.

OF MICHIG RICHARD L. DRAHN LAND SURVEYOR No. 21564 LARD

Date <u>May 29, 1996</u>