

SURVEY & REMONUMENTATION

SEP 08 1998

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in **SECTION**

<u>Gogebic</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T <u>48N</u> R <u>45W</u>	<u>C-11</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

Register's Office }
Gogebic County } ss.

Received for record the
18th day of JUNE
A. D. 1998 at 1:30 o'clock
P m., and recorded in
Liber 7 of CORNERS
on page 13
Barbara Collins Deputy
Register of Deeds

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

Section Corner 29, 30, 31 & 32; T.48 N., R.45 W.

I, Richard L. Drahn in a field survey on June 15, 19 98,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.**

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by Austin Burt on 9/27/1848. Original B.T.s --- Hemlock
12" S.62 E. 7 links (4.62') --- Hemlock 12" N.71 W. 23 links (15.18') ---
Corner restored by Donald D. Lappala (12585) on 4/8/63 from the remains of
the two original B.T.s and natural feature ties south and east. He set a
2" X 5' iron pipe with a 3" stamped brass cap and the following new B.T.s:

4"	Red Maple	S.69 W.	24.6'
4"	Red Maple	N.30 W.	26.9'
6"	Red Maple	N.42½ E.	25.6'

Corner recorded in Gogebic County in USFS Liber, Page V-5 on 4/1/64.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Corner research on file with Gogebic County records.

Recovered the monument as described and the bearing trees as follows:

9"	Red Maple	S.72 W.	24.63' (new nail)
6"	Red Maple	N.27 W.	26.78' " "
8"	Red Maple	N.43 E.	28.42' " "

No evidence remains of the original bearing trees.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

New bearing objects referenced:

5"	Red Maple	S.09 W.	37.73'
6'	Steel sign rail	N.50 W.	3.63'

PEER GROUP APPROVED

Richard L. Drahn 6/17/98
COUNTY REPRESENTATIVE



Signed by Richard L. Drahn

Date June 17, 1998

Surveyor's Michigan License No. 21564

USFS V-5

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1993