

MAR 02 2000

SECTION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office  
Gogebic County

For corners in

Gogebic Located In: Corner Code #  
(County)

1. Public Land Survey T 48N R 45W. J-3  
T R  
T R  
T R

2. Property Controlling S T R  
in Section S T R

3. Miscellaneous S T R  
Property in Sec. S T R

Received for record the  
21<sup>st</sup> day of JULY  
A. D. 1999 at 1:15 o'clock  
P. m., and recorded in  
Liber 7 of CORNER  
page 190  
Ramona Collins, Deputy  
Register of Deeds

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat  
5. Private Claims

Quarter Corner 2 & 11; T.48 N., R.45 W.

I, Richard L. Drahn, in a field survey on July 16, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by Austin Burt on 9/21/1848. Original bearing trees:

|         |     |          |          |          |
|---------|-----|----------|----------|----------|
| Elm     | 6"  | S.27° E. | 17 links | (11.22') |
| W. Pine | 36" | N.33° W. | 22 links | (14.52') |

Corner restored by Neal Sperhake, RLS 7876 on 11/9/61 from the remains of the W. Pine bearing tree. He set a 1" X 36" iron pipe monument and the following new bearing trees:

|          |     |          |           |          |
|----------|-----|----------|-----------|----------|
| Y. Birch | 16" | N.08° E. | 97 links  | (64.02') |
| Hemlock  | 8"  | S.41° W. | 65½ links | (43.23') |

Richard L. Drahn, RLS 21564 recovered Sperhakes' monument and new B.T.s on 9/21/82. He referenced the following new B.T.s:

|                 |     |          |        |
|-----------------|-----|----------|--------|
| Sugar Maple     | 7"  | N.35° E. | 4.85'  |
| Hemlock         | 10" | S.15° E. | 21.35' |
| Sugar Maple     | 7"  | S.55° W. | 13.10' |
| Metal sign post | 6'  | S.65° W. | 1.8'   |

Corner recorded in Gogebic County in Liber 2, Page 418 on 3/15/83.

Corner research on file with Gogebic County records.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I recovered Sperhakes' monument as described and his and Drahn's B.T.s as follows:

|                 |     |          |           |            |
|-----------------|-----|----------|-----------|------------|
| Yellow Birch    | 21' | N.11° E. | 63.87'    | (new nail) |
| Hemlock         | 14" | S.43° W. | Tree down |            |
| Sugar Maple     | 12" | N.45° E. | 4.85'     | (new nail) |
| Hemlock         | 13" | S.14° E. | 21.36'    | (new nail) |
| Sugar Maple     | 10" | S.58° W. | 13.07'    | (new nail) |
| Steel sign rail | 6'  | S.63° W. | 1.75'     |            |

No evidence remains of the original bearing trees.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

New bearing tree referenced:

|              |    |          |        |
|--------------|----|----------|--------|
| Yellow Birch | 5" | S.57° E. | 15.81' |
|--------------|----|----------|--------|

Signed by Richard L. Drahn Date July 20, 1999

Surveyor's Michigan License No. 21564

DEED GROUP APPROVAL

Richard L. Drahn 7/20/99  
COUNTY REPRESENTATIVE



FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1978  
REVISED JAN., 1983  
REVISED OCT., 1985