

MAR 02 2000

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Gogebic
(County)

Located in:

Corner Code #

1. Public Land Survey

T48N R46W

E-5

2. Property Controlling
in Section

S

T

R

3. Miscellaneous
Property in Sec.

S

T

R

S

T

R

S

T

R

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

Section Corner, Section 8,9,16,17, T48N,R46W

I, John P. Goss, in a field survey on July 2, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by Austin Burt on June 2, 1851.

Original bearing trees: Sugar 6" S 46° E 10 links (6.60')
Elm 18" N 46° W 8 links (5.28')

On June 8, 1981, Richard L. Drahn, RLS, restored corner position at found 1 1/4" iron pipe and original bearing tree (Sugar) and natural feature calles. He set a 2" aluminum monument with 3/4" aluminum cap, stamped to indicated the corner position. He established the following reference objects:

12" Sugar Maple N 62° W 23.00 ft.; 5" Sugar Maple N 57° E 17.00 ft.;
13" Sugar Maple S 69° E 12.43 ft.; 7' metal sign post S 62° W 2.4 ft.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

He recorded said corner in Liber 2, page 256 of Land Corners.

No original evidence found

Found Richard L. Drahn monument and accessories.

Act 74 research on file.

PEER GROUP APPROVED
Richard L. Drahn 7/20/99
COUNTY REGISTERED

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
From the found monument I established the following new and existing reference objects:

15" Sugar Maple N 62° W 23.12 ft. new nail
7" Sugar Maple N 57° E 16.98 ft.
16" Sugar Maple S 69° E 12.71 ft. new nail
12" Sugar Maple S 70° W 12.60 ft.
7' steel sign post S 62° W 2.4 ft. to face
(All measurement to nail in side of tree)

Signed by John P. Goss

Surveyor's Michigan License No. 23509

U.S.F.S. No. J-9

Date July 2, 1999

Register's Office } ss.
Gogebic County }

Received for record the
21st day of JULY
A. D. 1999 at 1:25 o'clock
P M., and recorded in
Liber 7 of CORNERS
on page 201
Ramona Collins, Deputy
Register of Deeds

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

