

MAR 02 2000

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office
Gogebic County

For corners in

Gogebic

(County)

Located In:

Corner Code #

1. Public Land Survey

T48N R46W

I-6

T R

T R

T R

T R

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

4. Lot No. , Recorded Plat

5. Private Claims

Quarter Corner 14 & 15, T.48 N., R.46 W.

I, John P. Goss, in a field survey on Sept. 1 19 99 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by Austin Burt, on May 28, 1851.

Original bearing trees: Cedar 10" S 75° W 29 links (19.14 ft.)
Cedar 11" N 68° E 20 links (13.20 ft.)

Richard L. Drahn, 21564, on October 17, 1979, restored corner at record bearing and distance from the Stump hole of the NE Cedar and other natural feature calls. He set a 2" iron pipe with 3" brass tablet, stamped to indicated the corner position. He established the following "reference" objects: 10" B. Ash S 56° W- 12.25 ft.; 10" Spruce - N 37° E - 23.2 feet; 12" B. Ash - S 89° E 12.05 ft.; 6' metal sign post - S 46° E - 1.8 ft.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

He recorded said corner in Liber 2, page 43 of Land Corners.

No original evidence found at this time.

Found Richard L. Drahn, monument and accessories.

Act 74 research on file.

DEED GROUP APPROVED

Richard L. Drahn 9/21/99
COUNTY REGISTRATION

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

From the found monument I established the following new and existing reference objects:

13" Black Ash	S 56° W	13.33 ft.	tree bend over now
16" Spruce	N 37° E	23.20 ft.	
13" Black Ash	S 89° E	11.82 ft.	
4" Elm	S 06° W	14.78 ft.	
6' metal sign post	S 46° E	1.8 ft.	to face

(All distance taken to nail in side of tree)

Signed by John P. Goss

Surveyor's Michigan License No. 23509

Date Sept. 1, 1999

U.S.F.S. No. L-17

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L
1												
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

