

MAR 02 2000

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office
Gogebic County ss.

For corners in

Gogebic

(County)

Located In:

Corner Code #

1. Public Land Survey

T.48^N R.46^W

I-9

2. Property Controlling
in Section

S

T

R

3. Miscellaneous
Property in Sec.

S

T

R

S

T

R

S

T

R

Received for record the

12TH day of MAY

A. D. 1999 at 10:20 o'clock

A m., and recorded in

Lib. 7 of CORNER

on page 146

Ramona Collins Deputy

Register of Deeds

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

Section corner 22, 23, 26 & 27, T.48N, R.46W

I, John P. Goss, in a field survey on May 3, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L
1												
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

A. Description of original monument and accessories and/or subsequent restoration:
Corner established by Austin Burt, U.S. Deputy Surveyor, on May 29, 1851.
Original bearing trees: Sugar 10" S 47° W 31 links (20.46')
Sugar 8" N 77½° E 43 links (28.38')

On Aug. 24, 1979, Richard L. Drahn, RLS, set corner from found 2" iron pipe at record bearing and distance from the remains of the two original bearing trees. He replaced the 2" iron pipe with a 2" iron pipe 5' long with a 3" brass tablet, stamped to indicate the corner position. He established the following reference objects: 6" S. Maple - N 17° W - 14.55'; 5" S. Maple - N 54° E - 26.5'; 5" S. Maple - S 41° W - 16.05'; 7' metal sign post - N 17° E 2.15'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
He recorded said corner in Liber 2, page 45 of Land Corners for Gogebic County.
Found Richard L. Drahn, monument and reference objects.

I updated the monument and accessories to state and county specification as note below.

Act 74 research on file.

DEER GROUP APPROVED
Richard L. Drahn 5/11/99
COUNTY REGISTER

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
From found monument I established the following existing and new reference objects:

9" Sugar Maple	N 17° W	14.67 ft.
7" Sugar Maple	N 54° E	26.55 ft.
7" Sugar Maple	S 41° W	16.03 ft.
9" Sugar Maple	S 32° E	29.50 ft.
7' metal sign post	N 17° E	2.25 ft. to face

(All measurement to nail in side of tree)



Signed by John P. Goss

Surveyor's Michigan License No. 23509

Date May 3, 1999

U.S.F.S. No. R-17