

MAR 08 2000

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office } ss.
Gogebic County }

For corners in

Gogebic
(County)

Located In:

Corner Code #

1. Public Land Survey

T 48N R 45W.

L-1

2. Property Controlling
in Section

S

T R

L-13

3. Miscellaneous
Property in Sec.

S

T R

S

T R

S

T R

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

Quarter corner 1 & 36; T.48-49 N., R.45 W.

I, Richard L. Drahn, in a field survey on July 30, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by Austin Burt on 9/9/1847. Original bearing trees:

Y. Birch	12"	N.67° E.	22 links	(14.52')
Sugar	16"	N.04° W.	29 links	(19.14')

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Restored corner position at record bearing and distance from the remains of the two original bearing trees. The first is a large series of root holes with Yellow Birch bark. The second one is now a large series of root holes with small clumps of very badly decayed Sugar Maple wood.

A 1" X 3' iron pipe and wood post bears S.11° E. 25.5'.

Corner research on file with Gogebic County records.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a 2" x 30" aluminum pipe monument with a 3 1/4" stamped aluminum cap and the following new B.T.s (all measurements taken to a nail in side of tree)

Sugar Maple	7"	N.32° W.	14.25'
Sugar Maple	8'	N.71° E.	25.55'
Sugar Maple	7"	S.62° W.	21.89'
Steel sign rail	6'	N.40 °E.	1.24'

DEER GROUP APPROVED

Richard L. Drahn 8/24/99
COUNTY REPRESENTATIVE

Signed by Richard L. Drahn Date August 10, 1999

Surveyor's Michigan License No. 21564

USFS A-23

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1976
REVISED JAN., 1983
REVISED OCT., 1985

Received for record the
26TH day of AUGUST
A. D. 1999 at 1:45 o'clock
P m., and recorded in
Lib. 7 of CORNERS
on page 235
Ramona Collins, Deputy
Register of Deeds

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

