

213

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
HOUGHTON
(County)

Located In:

Corner Code 44

1. Public Land Survey T R
T R
T R
T R
2. Property Controlling S 8 T 48N R 37W
In Section S T R
3. Miscellaneous S T R
Property In Sec. S T R

REGISTER'S OFFICE
Houghton County, Mich.

Received for record the 25 day
of April A.D. 1993 at 8:00
o'clock, A.M. and recorded in Vol. 3
of Survey Records Page 213
R. L. Drahn Register
Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

East 1/16 Corner, Sections 5, 8; T.48N., R.37W.

I, Richard L. Drahn, in a field survey on October 28, 19 93,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Not established in original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Established by single proportion on a line between the N.E. section corner and the
North 1/2 corner of Section 8, T.48N., R.37W.

SURVEY &
REMONUMENTATION

MAY 16 1997

COMMISSION



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a standard 2" diameter by 30" long split base aluminum
monument with a 3 1/2" aluminum cap stamped to read: T.48N., R.37W; E 1/16; S.5, S.8; 1993;
R.L.S. 21564: from which I established the following new blazed and scribed bearing
trees and/or reference objects:

8"	Black Ash	N.37°W.	11.0 feet
14"	Cedar	S.06°E.	35.80 feet
8"	Black Ash	S.57°W.	13.57 feet

A 6' steel sign post bears: S.04°E. 1.60 feet

Signed by Richard L. Drahn

Date February 16, 1994

Surveyor's Michigan License No. 21564