

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Houghton (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 33 T 51N R 36W	PCC S. of E11
	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. _____, Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 02/15/2012 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(PCC S. of E11) Property Controlling Corner marking the location of the Section line between Sections
32 and 33 at the south side of the West Branch of the Otter River. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(PCC) Established the position for the corner on the Section line between Section corner 888.00 ft.
north and Quarter corner 1702.09 ft. south.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(PCC) Set 1"IDx32" I.pipe with 4" alum. MDNR cap
stamped "P.O.L. Sec 32|Sec 33 T51N R36W"
Set measuring nail with MDNR tag in the side of:
9" B.Spruce N26E 16.5' mrkd "POL BT"
5" Cedar S58E 27.25' do
5" Spruce S50W 10.45' do
9" Cedar N52W 29.8' do
Set sq'd cedar post adjacent.
Bearings are magnetic.

Signed by Stephan J. Szyszkoski Date 03/07/2012
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division