

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

for corners in

Houghton (County)	Located In:	Corner Code #
Public Land Survey	T R	
	T R	
	T R	
Property Controlling Section	S 23 T 51N R 36W	4
	S 23 T 51N R 36W	11
	S T R	
Miscellaneous Property in Sec.	S T R	
	S T R	
Lot No. , Recorded Plat		
Private Claims		

Stephan J. Szyszkoski, in a field survey on 10/03/12 do hereby state  
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2  
above were in conformance with regulations and rules therefore as required in the current manual of survey  
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of  
Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with  
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,  
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded  
on this certificate.

1. Description of original monument and accessories and/or subsequent restoration:

(4-Sec. 23) Northwest 1/16 corner, Section 23. Not previously monumented.

(11-Sec. 23) Southwest 1/16 corner, Section 23. Not previously monumented.

2. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(4-Sec. 23) Established the position for the corner at the intersection of straight lines connecting  
opposite 1/16 corners.

(11-Sec. 23) Established the position for the corner at the intersection of straight lines  
connecting opposite 1/16 corners.

3. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(4) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
5" Sugar N44°E 31.3' mrkd "1/16S BT"  
16" Y.Birch S56°E 32.6' do  
3" Sugar S52°W 16.2' do  
3" Sugar N24°W 37.5' do  
Set sq'd cedar post adjacent.

(11) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
7" Sugar S63°E 20.1' mrkd "1/16S BT"  
9" Maple S31°W 7.5' do  
4" Sugar N83°W 11.0' do  
10" Maple N12°W 4.8' do  
Set sq'd cedar post adjacent.

Bearings are magnetic.

Signed by Stephan J. Szyszkoski  
Surveyor's Michigan License No. 33986

Date 01/09/2013

For the Michigan Department of Natural Resources, Forest Resources Division

