

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Houghton	Located In:	Corner Code #
(County)		
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 1 T 51N R 36W	4
	S 1 T 51N R 36W	5
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2		6		5		4		3		2			
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, Stephan J. Szyszkoski, in a field survey on 01/16/13 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(4-Sec. 1) Northwest 1/16 corner, Section 1. Not previously monumented.

(5-Sec. 1) North 1/16 corner, Section 1. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(4-Sec. 1) Established the position for the corner at the intersection of straight lines connecting opposite 1/16 corners.

(5-Sec. 1) Established the position for the corner on a straight line between Quarter corner 1372.56' north and the intersection of 1/4 lines of Section 1 1296.09' south, being 20 chains, proportionate to the dimensions given on and derived from the original plat, north of the Center of Section 1.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(4) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
5" Sugar N10W 15.3' mrkd "1/16S BT"
7" Sugar S50E 17.9' do
4" Sugar S11W 29.8' do
4" Sugar S86W 31.3' do
Set sq'd cedar post adjacent.
N=231075.984, E=7861093.221

(5) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
4" Sugar N56E 13.25' mrkd "1/16S BT"
17" Maple S49E 16.6' do
12" Hemlock S68W 10.5' do
11" Sugar N16W 10.8' do
Set sq'd cedar post adjacent.
N=231066.924, E=7861495.011

Bearings are magnetic. Coordinates are MCS83 in meters.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 02/07/2013

For the Michigan Department of Natural Resources, Forest Resources Division

