

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Houghton (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 9 T 51N R 36W	14 (GCDB 400520)
	S 9 T 51N R 36W	15 (GCDB 320500)
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. _____, Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 09/22/14 do hereby state  
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2  
above were in conformance with regulations and rules therefore as required in the current manual of survey  
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of  
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with  
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,  
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(14-Sec. 9) South 1/16 corner between Sections 9 and 10. Not previously monumented

(15-Sec. 9) West 1/16 corner between Sections 9 and 16. Not previously monumented



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(14-Sec. 9) Established the position for the corner midway and on the section line between Section  
corner 1372.11' south and Quarter corner 1372.11' north.

(15-Sec. 9) Established the position for the corner midway and on the section line between Section  
corner 1307.67' west and Quarter corner 1307.67' east.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(14) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
7" Sugar N53°E 17.4' mrkd "1/16S BT"  
4" Y.Birch S05°W 26.3' do  
7" Sugar S65°W 18.95' do  
6" Sugar N60°W 16.5' do  
Set sq'd cedar post adjacent.  
E= 7857363.052 N= 228803.192

(15) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
14" Sugar S69°E 19.25' mrkd "1/16S BT"  
14" Sugar South 10.9' do  
5" Sugar S77°W 6.2' do  
9" Sugar N12°W 12.55' do  
Set sq'd cedar post adjacent.  
E= 7856175.049 N= 228363.365

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum.  
Coord. Ref.=NGS PID RL0593: N= 221669.506 m. E= 7868965.488 m.

Signed by Stephan J. Szyszkoski  
Surveyor's Michigan License No. 33986

Date 03/12/2015

For the Michigan Department of Natural Resources, Forest Resources Division