

LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Stephan J. Szyszkoski

Field Survey Date: July 6, 2017

For corner(s) in: Houghton County

Original Public Land Survey Corner Corner Code
a. S T 51N R 36W H13 (GCDB 440100)

S T R
S T R
S T R

Property Corner 1/16 Corner Code
b. S 34 T 51N R 36W 16 (GCDB 460100)

S T R
S T R
S T R

1	A	B	C	D	E	F	G	H	I	J	K	L	M	1
2	6			5		4		3		2		1		2
3														3
4	7			8		9		10		11		12		4
5														5
6	18			17		16		15		14		13		6
7														7
8	19			20		21		22		23		24		8
9														9
10	30			29		28		27		26		25		10
11														11
12	31			32		33		34		35		36		12
13														13
	A	B	C	D	E	F	G	H	I	J	K	L	M	

Part A. Corner History

a.) Standard 1/4 corner on the 5th Correction line on the South side of Section 34, T51N-R36W. 1845 - Established by Austin Burt, Deputy, midway between Section corners 40.00 chains east and west and on the 5th Correction line. Set post. Cedar 14" N58°E 5 links, Sugar 12" N52°W 31 links.

b.) East 1/16 corner on the South line of Section 34, T51N-R36W. Not previously monumented.

Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

a.) The original post and accessories were not recovered. Found no evidence of the position of the original corner on the ground. Reestablished the position for the corner midway between Section corners 2633.43' east and west and on the 5th Correction line.

b.) Established the position for the corner midway and on the 5th Correction Line between Section corner 1316.72' east and Quarter corner 1316.72' west.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

a.) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
6" Sugar in clump N27°E 21.1' mrkd "1/4S NBT"
20" Sugar S53°E 8.95' do
6" Sugar N67°W 5.45' do
5" Sugar N28°W 8.2' do
Set sq'd cedar post adjacent.
E= 7858069.357 N= 221908.334

b.) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
12" Y.Birch N32°E 20.9' mrkd "1/16S BT"
8" Sugar S22°E 8.35' do
6" Sugar S27°W 5.9' do
5" Spruce N40°W 25.0' do
Set sq'd cedar post adjacent.
E= 7858470.531 N= 221897.960

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 date
Coord. Ref.=NGS PID RL0593: N= 221669.506 m. E= 7868965.488 m.

Stephan J. Szyszkoski

07/12/2017

Professional Surveyor's License No.: 33986

page 1 of 1

Prepared By: S.J. Szyszkoski for the Michigan Dept. of Natural Resources, 427 N. US41 Baraga, MI 49908

